

Hazardous Materials Technician

Skills Evaluation Sheets NFPA 1072 2017 Edition

STATE OF CONNECTICUT
COMMISSION ON FIRE PREVENTION AND CONTROL
860-627-6363
In-State Toll Free - 1-877-528-3473









Hazardous Materials/Weapons of Mass Destruction Technician Level – Skill Sheet Index

SS#	Skill Sheet Title	NFPA 1072 Objective Addressed
		2017 Edition
HMT-1	Analyze HMWMD Incident	7.1.2.2(1)(a-e)
HMT-2	Plan a Response	7.1.2.2(1)(a-e) 7.1.2.2(2)(a-e)
HMT-3	Implement a Planned Response	7.1.2.2(3)
HMT-4	Evaluate Progress and Terminate a Planned	7.1.2.2(4)(a)(b), 7.1.2.2(5)(a)(b)
THVII-4	Response	7.1.2.2(4)(a)(b), 7.1.2.2(3)(a)(b)
HMT-5	Donning SCBA	7.3.2(A)(1,4,5,9), 7.3.2B
HMT-6	Doffing SCBA	7.3.2(A)(1,4,5,9), 7.3.2B
HMT-7	SCBA – Ready for Immediate Use	7.3.2(A)(1,4,5,9), 7.3.2B
HMT-8	Decontamination Procedures and Techniques for Level A Entry Team	7.3.3B
HMT-9	Emergency Decontamination – Ambulatory	7.3.3B
HMT-10	Emergency Decontamination – Non- Ambulatory	7.3.3B
HMT-11A	Identify Railroad Cars	7.2.3B
HMT-11B	Identify Intermodal Tanks	7.2.1.1, 7.2.1.1.2(1)(a)(b)(2)(3)(a)(b)
HMT-11C	Identify Cargo Tanks	7.2.1.1, 7.2.1.1.3(1-7)
HMT-11D	Identify Facility Storage Tanks	7.2.1.1, 7.2.1.1.4(1-3)
HMT-11E	Identify Non-Bulk Packaging	7.2.1.1, 7.2.1.1.5(1-4)
HMT-11F	Identify Radioactive Material Packages	7.2.1.1, 7.2.1.1.6(1-5)
HMT-11G	Identify Bulk Containers	7.2.1.1, 7.2.1.1.7(1)(2)
HMT-12A	Container Markings on Transportation Vehicles	7.2.1.2, 7.2.1.2.1(1-3)
HMT-12B	Markings on Facility Containers	7.2.1.2, 7.2.1.2.2(1-3)
HMT-13	Analysis Process	7.2.1.3, 7.2.1.3.1, 7.2.1.3.2, 7.2.1.3.3(1-7), 7.2.1.3.4(1-18), 7.2.1.3.5(1-12), 7.2.1.3.6
HMT-14	Radioactive Identification	7.2.1.4
HMT-15	Collecting Samples	7.2.1.5(1-3)
HMT-16	Collecting and Interpreting Hazard and Response Information	7.2.2, 7.2.2.1(1-5), 7.2.2.2(1-54), 7.2.2.3, 7.2.2.4, 7.2.2.5, 7.2.2.6
HMT-17A	Bulk Container Construction	7.2.3, 7.2.3.1, 7.2.3.1.1(1)(a-g)(2)(a-c) (3)(4)(a-)(5)(6)(7)(a-d)
HMT-17B	Non-Bulk Container Construction	7.2.3, 7.2.3.1, 7.2.3.1.2(1-4)
HMT-17C	Radioactive Container Design and Testing Requirements	7.2.3, 7.2.3.1, 7.2.3.1.3(1-5)
HMT-18	Pipeline Identification	7.2.3, 7.2.3.2, 7.2.3.3
HMT-19	Identify Container Damage	7.2.3, 7.2.3.4
HMT-20	Radioactive Container Breach	7.2.3, 7.2.3.5
HMT-21A	Predict Likely Behavior of Material at Bulk Liquid Facility	7.2.4, 7.2.4.1, 7.2.4.2(1-6)
HMT-21B	Predict Likely Behavior at Bulk Gas Facility	7.2.4, 7.2.4.1, 7.2.4.3(1-4)
HMT-22	Estimating Likely Size of Endangered Area	7.2.5, 7.2.5.1, 7.2.5.2, 7.2.5.2.1 (1-14), 7.2.5.2.2, 7.2.5.3, 7.2.5.4
HMT-23	Planning the Response	7.3.1, 7.3.1.1, 7.3.1.2
HMT-24	Selecting Personal Protective Equipment	7.3.3, 7.3.3.1, 7.3.3.2(1-6), 7.3.3.3, 7.3.4, 7.3.3.4.1(1-3), 7.3.3.4.2, 7.3.3.4.3, 7.3.3.4.4(1-4), 7.3.3.4.5, 7.3.3.4.6, 7.3.3.4.7
HMT-26	Developing a Plan of Action	7.3.3.4.4(1-4), 7.3.3.4.5, 7.3.3.4.6, 7.3.3.4.7 7.3.5, 7.3.5.1(1-19), 7.3.5.2, 7.3.5.2, 7.3.5.2.1, 7.3.5.2.2, 7.3.5.3, 7.3.5.4, 7.3.5.5
HMT-27	Perform Incident Command Duties	7.4.1, 7.4.1.1, 7.4.1.2
HMT-28A	Use Protective Clothing and Respiratory Protection	7.4.2(1-4)
HMT-28B	Donning Level A Chemical Protective Clothing	7.4.2, 7.4.2(4)
HMT-28C	Doffing Level A Chemical Protective Clothing (Entry Personnel)	7.4.2, 7.4.2(4)
HMT-28D	Doffing Level "A" Suit (assistant)	7.4.2, 7.4.2(4)
HMT-28E	Donning Level B Clothing	7.4.2, 7.4.2(4)
HMT-28F	Doffing Level "B" Suit after Decontamination	7.4.2, 7.4.2(4)

HMT-29A1 Fusible Metal Plug Leak Containment – Bulk Vessel 7.4.3, 7.4.3(1)(a) HMT-29A2 Fusible Metal Plug Leak Containment – Non- Bulk 7.4.3, 7.4.3(1)(a) HMT-29B1 Fusible Metal Plug Threads Leak Containment – 7.4.3, 7.4.3(1)(b) Bulk Vessel Fusible Metal Plug Threads Leak Containment – 7.4.3, 7.4.3(1)(b) Non-Bulk Fusible Metal Plug Blowout – Bulk Vessel 7.4.3, 7.4.3(1)(b) HMT-29B3 Fusible Metal Plug Blowout – Bulk Vessel 7.4.3, 7.4.3(1)(b) HMT-29C1 Cylinder Sidewall Leak Containment (Horizontal) – 7.4.3, 7.4.3(1)(c) Bulk Vessel Fusible Metal Plug Blowout – Bulk Vessel 7.4.3, 7.4.3(1)(c) HMY-29C2 Cylinder Sidewall Leak Containment (Horizontal) – 7.4.3, 7.4.3(1)(c) Non-Bulk Vessel Fusible Metal Plug Blowout	
HMT-29B1Fusible Metal Plug Threads Leak Containment — Bulk Vessel7.4.3, 7.4.3(1)(b)HMT-29B2Fusible Metal Plug Threads Leak Containment — Non-Bulk7.4.3, 7.4.3(1)(b)HMT-29B3Fusible Metal Plug Blowout — Bulk Vessel7.4.3, 7.4.3(1)(b)HMT-29C1Cylinder Sidewall Leak Containment (Horizontal) — Bulk Vessel7.4.3, 7.4.3(1)(c)HMY-29C2Cylinder Sidewall Leak Containment (Horizontal) — Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D1Valve Blowout Leak Containment Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D2Valve Blowout (due to stripped threads) Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D3Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel7.4.3, 7.4.3(1)(d)	
Bulk Vessel HMT-29B2 Fusible Metal Plug Threads Leak Containment — 7.4.3, 7.4.3(1)(b) Non-Bulk HMT-29B3 Fusible Metal Plug Blowout – Bulk Vessel 7.4.3, 7.4.3(1)(b) HMT-29C1 Cylinder Sidewall Leak Containment (Horizontal) — 7.4.3, 7.4.3(1)(c) Bulk Vessel HMY-29C2 Cylinder Sidewall Leak Containment (Horizontal) — 7.4.3, 7.4.3(1)(c) Non-Bulk Vessel HMT-29D1 Valve Blowout Leak Containment Non-Bulk Vessel 7.4.3, 7.4.3(1)(d) HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk 7.4.3, 7.4.3(1)(d) Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel	
HMT-29B2Fusible Metal Plug Threads Leak Containment — Non-Bulk7.4.3, 7.4.3(1)(b)HMT-29B3Fusible Metal Plug Blowout — Bulk Vessel7.4.3, 7.4.3(1)(b)HMT-29C1Cylinder Sidewall Leak Containment (Horizontal) — Bulk Vessel7.4.3, 7.4.3(1)(c)HMY-29C2Cylinder Sidewall Leak Containment (Horizontal) — Non-Bulk Vessel7.4.3, 7.4.3(1)(c)HMT-29D1Valve Blowout Leak Containment Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D2Valve Blowout (due to stripped threads) Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D3Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel7.4.3, 7.4.3(1)(d)	
Non-Bulk	
HMT-29B3Fusible Metal Plug Blowout – Bulk Vessel7.4.3, 7.4.3(1)(b)HMT-29C1Cylinder Sidewall Leak Containment (Horizontal) – Bulk Vessel7.4.3, 7.4.3(1)(c)HMY-29C2Cylinder Sidewall Leak Containment (Horizontal) – Non-Bulk Vessel7.4.3, 7.4.3(1)(c)HMT-29D1Valve Blowout Leak Containment Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D2Valve Blowout (due to stripped threads) Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D3Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel7.4.3, 7.4.3(1)(d)	
HMT-29C1Cylinder Sidewall Leak Containment (Horizontal) – Bulk Vessel7.4.3, 7.4.3(1)(c)HMY-29C2Cylinder Sidewall Leak Containment (Horizontal) – Non-Bulk Vessel7.4.3, 7.4.3(1)(c)HMT-29D1Valve Blowout Leak Containment Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D2Valve Blowout (due to stripped threads) Non-Bulk Vessel7.4.3, 7.4.3(1)(d)HMT-29D3Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel7.4.3, 7.4.3(1)(d)	
Bulk Vessel HMY-29C2 Cylinder Sidewall Leak Containment (Horizontal) – 7.4.3, 7.4.3(1)(c) Non-Bulk Vessel HMT-29D1 Valve Blowout Leak Containment Non-Bulk Vessel 7.4.3, 7.4.3(1)(d) HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk 7.4.3, 7.4.3(1)(d) Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel	
HMY-29C2 Cylinder Sidewall Leak Containment (Horizontal) – 7.4.3, 7.4.3(1)(c) Non-Bulk Vessel HMT-29D1 Valve Blowout Leak Containment Non-Bulk Vessel 7.4.3, 7.4.3(1)(d) HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk 7.4.3, 7.4.3(1)(d) Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d)	
Non-Bulk Vessel HMT-29D1 Valve Blowout Leak Containment Non-Bulk Vessel 7.4.3, 7.4.3(1)(d) HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk 7.4.3, 7.4.3(1)(d) Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d)	
HMT-29D1 Valve Blowout Leak Containment Non-Bulk Vessel 7.4.3, 7.4.3(1)(d) HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk 7.4.3, 7.4.3(1)(d) Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d) 7.4.3, 7.4.3(1)(d)	
HMT-29D2 Valve Blowout (due to stripped threads) Non-Bulk Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d) 7.4.3, 7.4.3(1)(d)	
Vessel HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d)	
HMT-29D3 Valve Blowout Leak Containment (due to stripped threads) - Bulk Vessel 7.4.3, 7.4.3(1)(d)	
threads) - Bulk Vessel	
HMT-29E2 Valve Gland Stem Packing Leak Containment - 7.4.3, 7.4.3(1)(e)	
Non-Bulk Vessel	
HMT-29E3 Valve Stem Packing/Gland Leak Containment – 7.4.3, 7.4.3(1)(e)	
Bulk Vessel	
HMT-29F1 Valve Inlet Thread Leak Containment – Bulk Vessel 7.4.3, 7.4.3(1)(f)	
HMT-29F2 Valve Inlet Thread Leak Containment – Non-Bulk 7.4.3, 7.4.3(1)(f)	
Vessel	
HMT-29G1 Valve Seat Leak Containment – Bulk Vessel (valve 7.4.3, 7.4.3(1)(g)	
will not completely close)	
HMT-29G2 Valve Seat Leak Containment – Non-Bulk Vessel 7.4.3, 7.4.3(1)(g)	
(valve will not completely close)	
HMT-29H1 Valve Stem Assembly Blowout Leak Containment – 7.4.3, 7.4.3(1)(h)	
Bulk Vessel	
HMT-29H2 Valve Stem Assembly Blowout Leak Containment – 7.4.3, 7.4.3(1)(h) Non-Bulk Vessel	
HMT-29H3 Valve Broken Off Leak Containment – Bulk Vessel 7.4.3, 7.4.3(1)(h)	
HMT-29H4 Valve Stem Assembly Blowout or Broken Off Leak 7.4.3, 7.4.3(1)(h)	
Containment – Non-Bulk Vessel	
HMT-30A Close Open Valves on a Pressure Container 7.4.3, 7.4.3(2)(a)	
HMT-30B Replace Missing Plugs on a Pressure Container 7.4.3, 7.4.3(2)(b)	
HMT-30C Tighten Loose Plugs on a Pressure Container 7.4.3, 7.4.3(2)(c)	
HMT-31 Bung/Chime/Nail/Forklift Puncture Leak 7.4.3, 7.4.3(3)(a-d)	
Containment – 55 Gallon Drum	
HMT-32 Slide-in Over-pack – 55 Gallon Drum 7.4.3, 7.4.3(4)(a)(b)	
HMT-33 Slip-over Over-pack – 55 Gallon Drum 7.4.3.2(B)	
HMT-34 Grounding Procedures – Product Transfer Operation 7.4.3.4(B)	
7.4.3.8A Dome Cover Clamp Installation – Cargo Tank 7.4.3, 7.4.3(8)	
HMT-36 Perform Decontamination Operations 7.4.4.1(B), 7.4.4.2(B)	
HMT-37 Evaluating Progress of Control Functions and 7.5.1, 7.5.2	
Decontamination Process	
HMT-38A Assisting in Debriefing 7.6.1(1-4)	
HMT-38B Assisting in the Incident Critique 7.6.1(B)	
HMT-38C Reporting and Documenting the Incident 7.6.1(B)	

Rev. 9/12/18





Hazardous Materials Technician

Skill N	o. 	IMT-1	Primary Task:	Analyze a H	IMWMD Incident		
Object	tive(s)	7.1.2.2 (1)(a-e)	NFPA Star 1072, 2017		te No.	
			Perfor	mance Evaluation Sheet			
Tasks	:					1st	2nd
1.	Surve		WMD incident to identing through use of monit	fy containers, or classify materioring equipment	als, and verify presense		
2.			rprets hazard and resp oring equipment	oonse information from resource	es, electronic data		
3.	* Des	cribes type	and damage to contai	ners			
4.	* Predinvolv		ely behavior of release	d material and containers wher	n multiple materials are		
5.	Estim speci		f endangered area usii	ng computer modeling, monitori	ing equipment or		
* Critic	al Ste		re of this step mandates e on the entire objective	Safety is Paramount	Total number steps candi must complete to pass	date	4

Rev. 9/7/18





Hazardous Materials Technician

Skill N	Ю.	HMT-2	Primary Task:	Pla	an a Response		
Objec	tive(s): 7.1.2.	2 (2)(a-e)		A Standard: 2, 2017 Edition	Candidate No).
			Perfor	mance Evaluation SI	heet		
Tasks	s:					1	st 2nd
1.	Des	scribes res	sponse objectives for HMV	VMD incident			
2.	Des	scribes po	tential response objective	s for HMWMD incident			
3.	Sel	ects PPE	required for a given action	plan			
4.	Sel	ects techr	nical decontamination proc	ess to minimize hazard			
5.	* D	evelops aı	n action plan for HMWMD	incident			
6.	* D	esigns site	e safety and control plan				
* Criti	cal S		Failure of this step mandates	Safety is Paramount	Total number s	steps candidate	4

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-3	Primary Task:	Implement a F	Planned Res	sponse			
Objective	e(s): 7.1.2	2.2(3)(a-d)	NFPA Sta 1072, 201		Candidate No.			
		Perfo	rmance Evaluation Sheet					
Tasks:					1st	2nd		
	Performs of	duties of an assigned HM\	VMD branch or group position			1		
2. *	Dons, worl	ks in, and doffs appropriat	e PPE as needed					
3. P	erforms co	ontrol functions identified in	n action plan					
4. P	4. Performs decontamination functions identified in action plan							
* Critical	•	Failure of this step mandates failure on the entire objective	Safety is Paramount	Total number s	steps candidate to pass	3		

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-4	Primary Task:	Evaluate Prog	ress and Termi Response	nate a Planned	
Objective	e(s): 7.1.2.	2(4)(a)(b), 7.1.2.2(5)(a)(b)		FPA Standard: 072, 2017 Edition	Candidate No.	
		Perfor	mance Evaluation	Sheet		
Tasks:					1st	2nd
1. * [Evaluates e	ffectiveness of control fun	ctions			
2. Ev	/aluates eff	ectiveness of decontamina	ation process			
3. As	ssists in inc	ident debriefing				
4. As	ssists in inc	ident critque				
5. * F	Provides re	ports and documentation of	of incident			
* Critical		Failure of this step mandates	Safety is Paramour	Total number must complete	er steps candidate ete to pass	4

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill No. HMT-5 Primary Task: Donning SCBA				CBA				
Ob	jective(s	s): 7	.1.2.2, 7.1.2.2(3)(b), 7.4.2(3	3) NFPA Standard:	472, 2013 Edition	Candidate	No.	
			Perfo	ormance evaluation she	eet			
Tas	sk						1 st	2 nd
1	* Chec	ks cyli	nder gauge (90% Full)					
2	* Oper	ns cylin	der fully					
3 Dons harness								
4	Check	s facep	iece					
5	Conne	cts reg	ulator to facepiece					
6	Turns	PASS	device on					
7	Docum	nents a	ctivity log					
* C	ritical St	tep	Failure of this step mandates failure on the entire objective	Safety is PARAMOUN		ber steps cand plete to pass	lidate	5

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Ski	ll No.	HM	Г-6	Prir	nary Tas	k:		Doffing	SCBA		
Obj	ective(s): 7.	1.2.2, 7.1.2	2.2(3)(b), 7.4.2(3)	NFP	'A Standard:	1072, 2 Edition		Candidate	es No.	
				Perform	nance e	evaluation	shee	et			
Tas	sk									1 st	2 nd
1	* Maint	ains p	ositive pres	ssure in facepiec	e with reg	ulator attached					
2	* Leave	es cyli	nder fully o	pen							
3	Loosen	s harr	ness straps	from body							
4	4 Receives assistance from decon member to maintain and remove harness from the back to the front of the candidate										
5	Loosen	s face	epiece strap	os and removes f	acepiece	from face					
* C	ritical St	ер		is step mandates e entire objective	Safety is	PARAMOU	NT		er steps car lete to pass	ndidate	4

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	No.	HMT-7	Primary Task:	SCBA – Rea	ady for Imme	diate Use	
Obje	ective(s): 7.1.2.2, 7.1.2.2(3)(b), 7.4.2(3)	NFPA Standard:	1001 1072, 201	17 Edition Car	ndidate #	
			Performance Eva	luation Sheet			
Tas	sk						
						1st	2nd
1.	* Che	cks that cylinder is full (or a	nt least 90%)				
2.		ks operation of all gauges. e does not exceed 100 psi.	Verifies that the differ	ence between cyl	inder and regula	ator	
3.	Tests	operation of low pressure	alarm (to activate at 2	5% of cylinder)			
4.	Chec	ks all hose connections					
5.	Chec	ks condition of facepiece					
6.	Chec	ks condition of harness and	straps				
7.	Chec	ks operation of donning and	d bypass valves				
8.	Chec	ks that unit is clean and sar	nitized				
9.	* Tes	ts PASS device					
* Cri	itical S	tep Failure of this task mand failure on the entire obje		RAMOUNT	Total number ste		6

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill No. HN	/IT-8 Pr	Primary Task: Decontamination Procedures & Techniques For Level A Entry					
Objective(s):	7.1.2.2, 7.1.2.2(3)(d)	NFPA	Standard:	1072, 201 Edition	7 Candidate	No	
	Perfor	mance eva	luation	sheet			
Task							
Tubit						1 st	2 nd
1. Dons lev	rel "B" personal protective ed	luipment					
"PREFORI	MS DECON FOR LEVEL A	ENTRY TEAM"					
2. Performs							
3. Remove:	ner						
4. Performs	s suit and safety boots wash	and rinse					
5. Remove	s safety boots and fully enca	psulating suit					
6. Remove	s SCBA tank and harness, p	laces equipmer	nt in area for	later cleani	ing		
"LEVEL A	DRESS DOWN"						
7. Properly	removes (inside and out) ar	nd isolates dispo	sable PPE ((tape, outer	gloves, tyvek)		
8. Remove	s facepiece						
9. *Washes	s face and hands prior to ent	ering cold zone					
10. Takes բ	personal hygiene shower						
* Critical Step	Failure of this step mandates failure on the entire objective	Safety is PA	RAMOUN		number steps ca complete to pass		7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	Skill No. HMT-9 Primary Task: Emergency Decontamination - Ambul				Ambula	tory		
Obje	ective(s)	: 7.1.2.2, 7.1.2.2(2)		PA Standard:	1072, 201 Edition	7 Candidat	tes No.	
			Perfo	rmance ev	aluation sheet			
Task	•						1 st	2 nd
1	* Wear	s appropriate	protective clothing	properly				
2	Verbal	zes need for	emergency deconta	mination				
3	* Direc	ts victim from	contamination area					
4	Remov	ves victim's cl	lothing as rapidly as	possible				
5	Wash	exposed body	y parts immediately -	- flooding qua	antities of water			
6	Perforr	ns head-to-to	oe, gross, wash, and	rinse				
7	Establi	sh water run	off control if possible	•				
8	Transf	er victim to E	MS for assessment	and treatmen	t			
9	* Inforr	n EMS perso	nnel of contaminant	involved				
10	Docum	ent activity lo	og					
* Cri	tical Ste		of this step mandates n the entire objective	Safety is PA	ARAMOUNT	Total number steps car must complete to pass	ndidate	7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	No.	IMT-10	Primary Task:	Emergency Deco	ontamir	nation, Non-Amb	ulatory	
Obje	ective(s):	7.1.2.2, 7.1.2.2(2	N 2)(d)(3)(d)	NFPA Standard:1072	2017 Editio	Candida n	ites No.	
			Perfor	mance evaluati	on she	eet		
Task	k						1 st	2 nd
1	* Wears	appropriate	e protective clothing	properly				
2	2 Verbalizes need for emergency decontamination							
3	Removes victim to the emergency decontamination area							
4	Ensures victim is secure on roof ladder, stokes basket, skid or other device							
5	Wash fro	m head to	toe; gross, wash, ri	nse				
6			ated clothing while tact with any contar	ensuring, where praction	al, that th	ne victim does not		
7	Establish	n water run	off control if possib	le				
8	Instructs	responders	s to move victim to	clean area				
9	9 * Informs EMS personnel of contaminant, and its hazards if known							
10	Documen	ts activity log	g					
* Cri	tical Step		of this step mandates on the entire objective	Safety is PARAMO	UNT	Total number steps ca must complete to pass		7

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HMT-	-11A	Primary Task:	ld	lentify F	Railroad C	ars		
Objec	tive(s): 7.2	.1.1, 7.2	2.1.1.1(1-4)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluation	n Sheet				
Tasks	s:							1st	2nd
1.	Identifies of	containe	r name						
2.	* Identifies	the con	ntainer by specificatio	ns					
3. Identifies the typical contents by name									
4.	4. Identifies the typical contents by hazard class								
* Critic	cal Step		of this step mandates	Safety is Paramo u	ınt	Total number	r steps candid te to pass	ate	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-11E	B Primary Task:		Identify Int	ermodal T	anks		
Objective	e(s): 7.2.1.1,	, 7.2.1.1.2(1)(a)(b)(2)(3)(a)(b)	NFPA Sta 1072, 201		Candidate	No.	
		Perfor	mance Evalua	tion Sheet				
Tasks:							1st	2nd
	lentifies conta	ainer name					100	ZHG
2. *	Identifies the	container by specification	ons					
	lentifies the ty	ypical contents by name						
	lentifies the ty	ypical contents by hazard	d class					
								<u>I</u>
* Critical	Sten -	ilium of this other considers.	_	, 1	Total number	steps candid	ate	
Cillical	Failure of this step mandates failure on the entire objective		Safety is Parar	nount	must complet		ulb	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No	o. HMT- 1	11C	Primary Task:		Identify (Cargo Tan	ks		
Object	ive(s): 7.2.	1.1, 7.2	2.1.1.3(1-7)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluati	on Sheet				
Tasks:	:							1st	2nd
	Identifies co	ontaine	r name						
2.	* Identifies t	the con	ntainer by specificatio	ns					
3.	3. Identifies the typical contents by name								
4.	4. Identifies the typical contents by hazard class								
* Critic	al Step		of this step mandates on the entire objective	Safety is Paramo	ount	Total number must complet		ate	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No	o. HMT- 1	11D	Primary Task:		Identify Facili	ity Storage	Tanks		
Objecti	ive(s): 7.2.	1.1, 7.2	2.1.1.4(1-3)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Eva	aluation Sheet				
Tasks:								1st	2nd
1.	Identifies co	ontaine	r name						
2.	* Identifies t	the con	ntainer by specification	ons					
3.	3. Identifies the typical contents by name								
4.	4. Identifies the typical contents by hazard class								
* Critic	* Critical Step Failure of this step mandates failure on the entire objective			Safety is Pa	aramount	Total number must complet		ate	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-11E	Primary Task:	Identify No	n-Bulk Pac	kaging			
Objective	e(s): 7.2.1.1, 7.	2.1.1.5(1-4)		Standard: 017 Edition	Candidate	No.		
		Perfor	mance Evaluation She	et				
Tasks:						1 o t	Cod	
	entifies containe	ar nama				1st	2nd	
2. * 1	dentifies the co	ntainer by specificatio	ns					
3. ld	3. Identifies the typical contents by name							
4. Identifies the typical contents by hazard class								
* Critical	•	e of this step mandates on the entire objective	Safety is Paramount	Total number	er steps candidate	ate	3	

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-11F	Primary Task:	Identify Radioactiv	ve Materia	ls Package:	s	
Objective	e(s): 7.2.1.1, 7.	2.1.1.6(1-5)	NFPA Sta 1072, 201		Candidate N	۱o.	
		Perfor	mance Evaluation Sheet				
Tasks:						1st	2nd
	entifies contain	er name				101	2110
2. * I	dentifies the co	ntainer by specification	ns				
	entifies the typi	cal contents by name					
	entifies the typi	cal contents by hazard	d class				
* Critical	Stop - "			Total number	steps candidate		
Cilical	•	e of this step mandates on the entire objective	Safety is Paramount	must complet		-	3

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HMT- 1	11G	Primary Task:	Id	entify Bu	ulk Contair	ners		
Object	tive(s): 7.2.	1.1, 7.2	.1.1.7(1)(2))		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluation	on Sheet				
Tasks	s :							1st	2nd
1.	Identifies co	ontainer	r name						
2.	* Identifies	the con	tainer by specificatio	ns					
3.	3. Identifies the typical contents by name								
4.	4. Identifies the typical contents by hazard class								
									ļ
* Critic	cal Step		of this step mandates	Safety is Paramo	unt	Total number must complet		ate	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No	o. HMT-	12A	Primary Task:	Container Mar	kings or	n Transpoi	rtation Ve	hicle	S
Objecti	ive(s): 7.2.	1.2, 7.2	2.1.2.1(1-3)		NFPA Star 1072, 201		Candidate	No.	
			Perfor	mance Evaluatio	n Sheet				
Tasks:	:							1st	2nd
1.	Identifies m	arkings	s on container						
2.	* Identifies	capacit	ty						
3.	3. Identifies other available resources to assist in process								
* Critica	al Step		of this step mandates	Safety is Paramou	ınt	Total number		ate	2

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-12B	Primary Task:	Container Markings	s on Facility C	ontainers	
Objectiv	re(s): 7.2.1.2, 7	7.2.1.2.2(1-3)	NFPA Sta 1072, 201		ndidate No.	
		Perfor	mance Evaluation Sheet	:		
Tasks:					1st	2nd
1. lo	dentifies markin	ngs on container				
2. lo	dentifies capaci	ty				
3. lo	dentifies other a	available resources to a	assist in process			
* Critica		re of this step mandates e on the entire objective	Safety is Paramount	Total number steps		2

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No). H I	MT-13	13 Primary Task: Analysis Process						
Objectiv	ve(s):		7.2.1.3.1, 7.2.1.3.2, 7.2 4(1-18), 7.2.1.3.5(1-12)		NFPA Star 1072, 2017		Candidate	No.	
			Perfo	rmance Eval	uation Sheet				
Tasks:								1st	2nd
1. I	Identifi	ies steps f	for classifying by haza	rd an unknown s	solid				
2. I	Identifi	ies steps	for classifying by haza	rd an unknown I	iquid				
3. I	Identifi	ies steps	for classifying by haza	rd an unknown a	atomsphere				
4. I	Identifi	es type(s	s) of monitoring technol	logy used to det	ermine specific h	azards			
Identifies and determines limiting factors associated with monitoring equipment, test strips and reagents							t strips and		
 * Selects and demonstrates correct techniques for monitoring equipment, test strips and/or reagents to identify hazards 									
		onstrates agents	field maintenance and	I testing procedu	ures for monitorin	g equipment	, test strips		
* Critica	* Critical Step		ure of this step mandates	Safety is Par	amount	Total number	r steps candidate to pass	ate	5

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-1	4	Primary Task:		Radioactiv	e Identifica	ation		
Objective	e(s): 7.2.1	.4			NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evalua	ation Sheet				
Tasks:								1st	2nd
1. Id	entfies typ	e or ca	tegory of label for ra	dioactive materia	al				
2. Id	entifies co	ntents	of product						
3. Id	3. Identifies activity of product								
4. Id	4. Identifies transport index of product								
5. * Identifies criticality index of product									
6. * Describes the radiation dose rates associated with each label									
* Critical			of this step mandates in the entire objective	Safety is Para	mount	Total number must complet		ate	4

Rev. 9/7/18





Hazardous Materials Technician

Skill N	Skill No. HMT-15 Pr		Primary Task:	Со	llecting Sar	mples		
Objec	tive(s): 7.2.	1.5(1-3))		PA Standard: '2, 2017 Editior	Candidate n	No.	
			Perfor	mance Evaluation S	heet			
Table							4-4	2-4
Tasks							1st	2nd
1.	* Demonstr	ates ap	propriate methods fo	or collecting a gas based	on product			
2.	* Demonstr	ates ap	propriate methods for	or collecting a liquid base	d on product			
3.	3. * Demonstrates appropriate methods for collecting a solid based on product							
* Critic	Critical Step		of this step mandates on the entire objective	Safety is Paramount		umber steps candida	ate	3

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HI	MT-16	Primary Task:	Collecting and	-	ting Hazar rmation	d and Re	spon	se
Objec	tive(s):	7.2.2, 7.2.2 7.2.2.5, 7.2	2.1(1-5), 7.2.2.2(1-54) 2.2.6	, 7.2.2.3, 7.2.2.4,	NFPA Sta 1072, 201		Candidate	No.	
			Perfori	mance Evaluati	on Sheet				
Tasks	s:							1st	2nd
1.			rprets types of hazard ges and disadvantage		mation from	resources a	nd		
2.	Descri	bes termino	ology and explains sig	nificance in the ana	lysis proces	s			
3.	Describes heat transfer processes that occur as a result of a cryogenic liquid spill								
4.	4. * Identifies signs and symptoms of exposure to material and the target organ effects								
5. * Identifies methods for determining pressure in bulk packaging or facility containers									
Identifies method for determining amount of lading remaining in damaged bulk packaging or facility containers									
* Critic	cal Step	Step Failure of this step mandates failure on the entire objective Safety is Paramount Total number stemust complete to						late	4

Rev. 9/7/18





Hazardous Materials Technician

Skill No. HMT-17A Primary Task: Bulk Container Construction									
Objectiv	ve(s):	7.2.3, 7.2.3 (4)(a-c)(5)	3.1, 7.2.3.1.1(1)(a-g)((6)(7)(a-d)	2)(a-c)(3)	NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evalua	tion Sheet	:			
Tasks:								1st	2nd
1. I	dentif	ies basic de	esign and construction	features of cargo	tanks				
2.	' Iden	tifies closure	es of cargo tanks						
3. I	dentif	ies basic de	esign and construction	features of fixed	facility tanks				
4.	' Iden	tifies closure	es of fixed facility tank	S					
5. I	dentif	ies basic de	esign and construction	features of intern	nediate bulk o	containers			
6.	' Iden	tifies closure	es of intermediate bul	k containers					
7. I	dentif	ies basic de	esign and construction	features of intern	nodal tanks				
8.	' Iden	tifies closure	es of intermodal tanks	;					
9. l	dentif	ies basic de	esign and construction	features of one-t	on containers	3			
10.	' Iden	tifies closure	es of one-ton containe	ers					
11. I	dentif	ies basic de	esign and construction	features of pipeli	nes				
12.	' Iden	tifies closure	es of pipelines						
13. I	dentif	ies basic de	esign and construction	features of railro	ad cars				
14. '	' Iden	tifies closure	es of railroad cars						
* Critica	al Step		of this step mandates on the entire objective	Safety is Paran	nount	Total number must complet	steps candidate to pass	ate	10

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HM1	Г-17B	Primary Task:	Non-B	Bulk Cont	ainer Con	struction		
Objec	tive(s): 7.	2.3, 7.2.	3.1, 7.2.3.1.2(1-4)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluati	on Sheet				
Tasks	S :							1st	2nd
1.	Identifies	basic de	esign and construction	n features of bags					
2.	* Identifie	s closure	es of bags						
3.	Identifies	basic de	esign and construction	n features of carboys	5				
4.	* Identifie	s closure	es of carboys						
5.	5. Identifies basic design and construction features of drums								
6.	* Identifie	s closure	es of drums						
7.	Identifies	basic de	esign and construction	n features of cylinder	rs				
8.	* Identifie	s closure	es of cylinders						
* (-:: 4:	aal Ctara					Total number	r otopo popdid	oto	
" Critic	cal Step		of this step mandates on the entire objective	Safety is Paramo	ount	must comple	r steps candid te to pass	ate	6

Rev. 9/7/18





Hazardous Materials Technician

Skill No	^{o.} HMT-1	17C	Primary Task:	Radioactiv		ner Design iirements	and Test	ing	
Objecti	ive(s): 7.2.3	3, 7.2.3	3.1, 7.2.3.1.3(1-5)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluation	on Sheet				
Tasks:	:							1st	2nd
1.	Identifies ba	asic de	sign and construction	n features of excepte	d package:	S			
2.	* Identifies t	testing	requirements of exce	epted packages					
3.	Identifies ba	asic de	sign and construction	n features of industria	al packages	S			
4.	* Identifies t	testing	requirements of indu	ıstrial packages					
5.	5. Identifies basic design and construction features of Type A								
6.	* Identifies testing requirements of Type A								
7.	Identifies ba	asic de	sign and construction	n features of Type B					
8.	* Identifies t	testing	requirements of Typ	е В					
9.	Identifies ba	asic de	sign and construction	n features of Type C					
10.	* Identifies t	testing	requirements of Typ	e C					
* Critic	al Step		of this step mandates on the entire objective	Safety is Paramo	unt	Total number s	•	ate	7

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HI	MT-18	Primary Task:		Pipeline I	dentificati	on		
Objec	tive(s):	7.2.3, 7.2.	.3.2, 7.2.3.3(1-4)		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluat	ion Sheet				
Tasks	s:							1st	2nd
1.	Descri	bes how lic	quid petroleum produc	t pipeline carries di	fferent produ	ıct			
2.	Identifi	es owners	hip of pipeline						
3.	3. * Identifies procedures for checking gas migration								
4.	4. * Identifies procedures for shutting down pipeline or contolling leak								
5.	5. Identifies type of product in pipeline								
* Critic	Critical Step		Step Failure of this step mandates failure on the entire objective Safety is Paramount Total number steps car must complete to pass			ate	4		

Rev. 9/7/18





Hazardous Materials Technician

Skill N	Skill No. HM		9 P	rimary Task:	Identif	fy Cor	ntainer Da	amage		
Object	tive(s): 7.2.3,	7.2.3.4			PA Sta 72, 201	ndard: 7 Edition	Candidat	e No.	
				Perfor	mance Evaluation S	Sheet				
Tasks):								1st	2nd
1.	* De	escribes t	he visua	al and predictable	characteristics of a "Stre	ss Ever	nt" on a cont	tainer		
2.	* De	escribes tl	he visua	al and predictable	characteristics of a "Brea	ach Eve	nt" on a con	ntainer		
3.	* Describes the visual and predictable characteristics of a "Release Event" on a container							ntainer		
4.	4. * Describes the visual and predictable characteristics of an "Engulf Event" on a container							ntainer		
5.	5. * Describes the visual and predictable characteristics of an "Impinge Event" on a container							ontainer		
6.	6. * Describes the visual and predictable characteristics of a "Harm Event" on a container									
* Critic	cal St	•		his step mandates he entire objective	Safety is Paramount	t	Total number must comple	er steps candic ete to pass	date	6

Rev. 9/7/18





Hazardous Materials Technician

Skill No.	HMT-2	20	Primary Task:	Rad	lioactive (Container E	Breach		
Objectiv	/e(s): 7.2.3	3, 7.2.3.	.5		NFPA Sta 1072, 201		Candidate	e No.	
			Perfor	mance Evaluati	ion Sheet				
Tasks:								1st	2nd
1. S	Surveys are	ea and s	situation surrounding	radioactive contain	ner breach				
2. *	Uses appr	ropriate	monitoring equipme	ent to survey area a	nd containe	r			
3. D	3. Determines intregrity of container								
4. D	4. Determines a breach has occurred								
* Critical	Critical Step Failure of this step mandates failure on the entire objective Safety				ount	Total number must complete		late	3

Rev. 9/7/18





Hazardous Materials Technician

Skill N	^{о.} НМТ- 2	21A	Primary Task:	Predict Likely		of Mater cility	ial at Bulk	c Liqu	id
Object	ive(s): 7.2.	4, 7.2.4	1.1, 7.2.4.2(1-6)		NFPA Stan 1072, 2017		Candidate	e No.	
			Perfo	rmance Evaluation	on Sheet				
Tasks	:							1st	2nd
1.	Identifies th	ree res	sources available th	at indicates the effect	s of mixing v	arious mate	erials		
2.	* Identifies	impact	of fire and safety fe	eatures on behavior of	products at	bulk liquid f	acility		
3.	Explain sigi	nificand	e of fire protection	systems in analysis p	rocess				
4.	Explain sigr	nificano	e of monitoring and	d detection systems in	analysis pro	ocess			
5.	Explain sigi	nificand	ce of pressure relief	and vacuum relief pro	otection in ar	nalysis proc	ess		
6.	6. Explain significance of product spillage and contol in analysis process								
7.	Explain sigi	nificand	ce of tank spacing in	n analysis process					
8.	Explain sigi	nificano	ce of transfer operat	tions in analysis proce	ess				
* Critic	Critical Step Failure of this step mandates failure on the entire objective Safety is Paramount Total number steps candid must complete to pass						date	6	

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo. HMT-2	1B Primary Task:	Predict Likely Behavio Fa	or of Mater acility	rial at Bull	k Gas	5		
Objec	tive(s): 7.2.4	, 7.2.4.1, 7.2.4.3(1-4)	NFPA Star 1072, 2017		Candidate	No.			
		Perfor	mance Evaluation Sheet						
Tasks	s:					1st	2nd		
1.	Identifies thr	ee resources available tha	t indicates the effects of mixing	various mate	rials				
2.	2. * Identifies impact of fire and safety features on behavior of products at bulk gas facility								
3.	3. Explain significance of fire protection systems in analysis process								
4.	4. Explain significance of monitoring and detection systems in analysis process								
5. Explain significance of pressure relief protection in analysis process									
6.	Explain sign	ificance of transfer operation	ons in analysis process						
					_				
* Critic	Critical Step Failure of this step mandates failure on the entire objective Safety is Paramount Total number steps candid must complete to pass						4		

Rev. 9/7/18





Hazardous Materials Technician

Skill No). H l	MT-22	Primary Task:	Estimating	J Likely S	ize of Enda	ingered A	Area	
Objectiv	ve(s):	7.2.5, 7.2.5 7.2.5.3, 7.2	5.1, 7.2.5.2, 7.2.5.2.1 2.5.4	(1-14), 7.2.5.2.2,	NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluati	on Sheet				
Tasks:								1st	2nd
1. I	Identifi	es resource	es for dispersion patte	ern prediction and m	nodeling				
2.	* Ident	ifies steps fo	or determining likely (extent of physical, s	afety and he	ealth hazards			
3. I	Descri	bes termino	logy and exposure va	alues and explains s	significance	in the analysis	s process		
4. I	Identifi	es methods	for predicting areas	of potential harm wi	ithin endang	ered area			
5. I	Identifi	es steps for	estimating outcomes	s within endangered	d area				
6. l	Detern	nines applic	able public protective	response options a	and the area	to protect			
* Critica	al Step		of this step mandates	Safety is Param e	ount	Total number		ate	4

Rev. 9/7/18





Hazardous Materials Technician

Skill N	lo.	HMT-23	Primary Task:		Planning 1	he Respor	nse		
Objec	tive(s): 7.3.1, 7	7.3.1.1, 7.3.1.2		NFPA Sta 1072, 201		Candidate	No.	
			Perfor	mance Evaluat	ion Sheet				
Tasks	s:							1st	2nd
1.	Ide	ntifies or de	evelopes the response ob	jective for each pr	oblem				
2.	* D	escribes the	e steps for determining re	esponse objective(s)				
3.	3. Identifies possible response options by response objective for each problem								
4. Identifies the possible response options to accomplish a given response objective									
5. Makes recommendations for the response objectives and response options to the I.C.									
* Critical Step Failure of this step mandates failure on the entire objective			ount	Total number		ate	4		

Rev. 9/7/18





Hazardous Materials Technician

Skill N	o. F	IMT-24	Primary Task:	Selecting Persona	al Protective Equipment				
Object	tive(s)	7.3.2		NFPA Sta 1072, 201		Candidate N	lo.		
			Perfor	mance Evaluation Sheet					
Tasks	:						1st	2nd	
1.	Ident	fies and des	scribes the four (4) lev	els of PPE as specified by EPA	and NIOSH				
2.	* Ider		escribes PPE options	available based on type(s) of h	arm at HMWMI				
3.	Identifies process when considering the selection of respiratory protection for a specified action option								
4.	Describes terms and explains impact and significance on selection of chemical-protective clothing								
5.	Ident	fies at least	three indications of m	aterial degradation of chemical	-protective clot	hing			
6.	* Ider	tifies the di	fferent designs of vapo	or-protective and splash-protect	tive clothing				
7.	Desc	ribes advan	tages and disadvantaç	ges to vapor-protective and spla	ash-protective o	clothing			
8.	Ident	fies process	s for selecting protective	ve clothing for HMWMD inciden	ts				
9.			protective clothing co	nstruction materials for a given	action option u	sing			
10.	Ident	fies the phy	siological and psychol	ogical stresses that can affect u	users of PPE				
						_			
* Critic	Critical Step Failure of this step mandates failure on the entire objective Safety is Paramount Total number steps candidate must complete to pass							7	

Rev. 9/7/18





Hazardous Materials Technician

Skill No. HMT-25 Primary Task: Decontamination Method Selection																	
Object	tive(s	s): 7.3.:	3B									ndard: 7 Editi		Cai	ndidat	te No.	
					l	Perfor	mano	e Ev	aluat	ion SI	heet						
Tasks	::															1st	2nd
1.		ermines Ived.	best	t method	d of dec	ontamir	ation I	based	on inc	ident ty	pe ar	nd mat	erial/m	nateria	als		
2.				ability to operation		and im	olemer	nt tech	nical c	deconta	minat	ion op	eratio	ns in			
3.				ability to			olemer	nt tech	nical c	deconta	minat	ion op	eratio	ns inv	olving		
4.				ability to			olemer	nt mas	s deco	ontamin	ation	opera	tions i	nvolvii	ng		
* Critic	cal S	tep		re of this s			Safet	ty is P	aram	ount			numbe comple			date	3

Rev. 9/7/18





Hazardous Materials Technician

Skill No. HMT-26 Primary Task: Developing a Plan of Action									
Objecti	ve(s): 7.3.4				NFPA Star 1072, 2017		Candidate	No.	
			Perfor	mance Evaluation	n Sheet				
Tasks:								1st	2nd
			of, procedures for, HMWMD control	equipment required f	or, and safe	ty precautio	ons used		
2.	* Develops i	ncident	action plan includir	ng site safety and cor	ntrol plan				
3.	* Lists and d	lescribe	es the safety consid	erations based on the	e incident a	nd action pla	an		
4.	* Identifies p	oints th	at should be made	in a safety briefing p	rior to worki	ng at the sc	ene		
	Identifies atmospheric and phyiscal safety hazards associated with HMWMD incidents involving confined space								
6. l	dentifies pre-entry activities to be performed								
	Identifies pro evidence at l			safety precautions fo	r preserving	and collect	ting legal		
* Critica			f this step mandates the entire objective	Safety is Paramo	unt	Total numbe must comple	r steps candid ete to pass	ate	5

Rev. 9/7/18





Hazardous Materials Technician

Skill No. HMT-27 Primary Task: Perform Incident Command Duties									
Objective	e(s): 7.4.1	1, 7.4.1.1, 7.4.1.2	2		NFPA Sta 2013 Editi	ndard: 472, on	Candidate	No.	
			Perfor	mance Evaluati	on Sheet				
Tasks:								1st	2nd
1. In	itiates IMS	S/ICS at HMWMI	D incidents	according to policie	s and proce	dures of AHJ			
2. *	Demonstra	ates duties of as	signed fund	ction at HMWMD inc	ident				
3. Id	lentifies ro	les at HMWMD i	incident						
4. D	ocuments	all aspects of IM	1S/ICS as e	stablished by policie	es and proc	edures of AH.	I		
_{5.} C	ommunica	ntes observations	s to hazmat	branch director/gro	up supervis	or			
* Critical	Step	Failure of this step r failure on the entire		Safety is Paramo	ount	Total number must complete		ate	4

Rev. 9/7/18





Hazardous Materials Technician

Skill No. HMT-28A Primary Task: Use Protective Clothing and Respiratory Protection							ion
Objectiv	/e(s): 7.4.2(1,2)			NFPA Standard: 1072, 2017 Edition	Candidate	No.	
		Perfo	rmance Evaluatio	n Sheet			
Tasks:						1st	2nd
1. [Describes three s	safety procedures for	personnel working in o	chemical-protective cl	othing		
2.	Describes three e	emergency procedure	es for personnel workin	g in chemical-protect	ive clothing		
3. r	Demonstrates a espiratory protect	ability to don, work in, ction provided by AH.	and doff self-containe	d breathing apparatus	s or other		
			and doff liquid splash- specialized protective e				
* Critica	•	e of this step mandates	Safety is Paramou	Total number must complete	er steps candida ete to pass	ate	3

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Objective(s): 7.4.2, NFPA Standard: 1072, 2017 Edition Sheet Performance evaluation sheet THE FOLLOWING PROCEDURES ASSUME THAT PEROR TO THE CHEMICAL PROTECTIVE CLOTHING BEING DOWNED, IT HAS BEEN PROPERLY TESTED AND INSPECTED AS PER MANUFACTURER'S SPECIFICATION AS HAS THE SCEA MUICH WILL BE MOON Task: For people dressing entry team members 1 st 2 nd Removes personal effects which might result in damage of the suit Adjusts hard hat or face piece, if worn. Removes until SCBA is in place Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist The Puts on chemical resistant boots over feet of suit Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat, if applicable Raises hood over head carefully. Adjusts for comfortable fit Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals 2 *Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates failure on the entire objective failure on the failure of the failure of the failure of the failure on the failure of the failure of the f	Skill	No. HMT-28B	Primary Task:	Donning Leve	el A Chemical Protectiv	ve Cloth	ning
THE FOLLOWING PROCEDURES ASSUME THAT PRIOR TO THE CHEMICAL PROTECTIVE CLOTHING BEING DONNED, IT HAS BEEN PROPERLY TESTED AND INSPECTED AS PER MANUFACTURER'S SPECIFICATION AS HAS THE SCBA MHICH WILL BE WORN Task: For people dressing entry team members 1 st 2 nd Removes personal effects which might result in damage of the suit Adjusts hard hat or face piece, if worn. Removes until SCBA is in place Don cooling equipment, if worn Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist Puts on chemical resistant boots over feet of suit Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals *Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	Obje	ective(s): 7.4.2,			Candidat	te No.	
Task: For people dressing entry team members 1 st 2 nd Removes personal effects which might result in damage of the suit Adjusts hard hat or face piece, if worn. Removes until SCBA is in place Don cooling equipment, if worn Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist *Puts on chemical resistant boots over feet of suit Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals *Connects breathing hose, opens main valve *Assistant verifies proper breathing, makes final closure of suit, checks all fasteners *Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate			Performance eva	luation she	eet		
1 Removes personal effects which might result in damage of the suit 2 Adjusts hard hat or face piece, if worn. Removes until SCBA is in place 3 Don cooling equipment, if worn 4 Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist 5 *Puts on chemical resistant boots over feet of suit 6 Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank 7 Performs negative and positive facepiece seal tests 8 Puts on inner gloves or secures detachable gloves to suit 9 Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable 10 Raises hood over head carefully. Adjusts for comfortable fit 11 *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals 12 *Connects breathing hose, opens main valve 13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10					-		
2 Adjusts hard hat or face piece, if worn. Removes until SCBA is in place 3 Don cooling equipment, if worn 4 Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist 5 *Puts on chemical resistant boots over feet of suit 6 Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank 7 Performs negative and positive facepiece seal tests 8 Puts on inner gloves or secures detachable gloves to suit 9 Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable 10 Raises hood over head carefully. Adjusts for comfortable fit 11 *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals 12 *Connects breathing hose, opens main valve 13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10	Tas	k:	For people dressing e	ntry team membe	ers	1 st	2 nd
3 Don cooling equipment, if worn 4 Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist 5 *Puts on chemical resistant boots over feet of suit 6 Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank 7 Performs negative and positive facepiece seal tests 8 Puts on inner gloves or secures detachable gloves to suit 9 Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable 10 Raises hood over head carefully. Adjusts for comfortable fit 11 *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals 12 *Connects breathing hose, opens main valve 13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10	1	Removes personal effects	which might result in dama	age of the suit			
Standing or sitting, steps into legs of suit, ensures proper placement of feet within suit, then gathers suit up around waist * Puts on chemical resistant boots over feet of suit Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners * Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10	2	Adjusts hard hat or face pie	ece, if worn. Removes unti	I SCBA is in place	•		
gathers suit up around waist * Puts on chemical resistant boots over feet of suit Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners * Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	3	Don cooling equipment, if v	vorn				
Dons SCBA. Adjusts facepiece. Does not connect breathing hose. Opens tank Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners * Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	4			oper placement of	feet within suit, then		
Performs negative and positive facepiece seal tests Puts on inner gloves or secures detachable gloves to suit Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit *Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals *Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners *Assistant observes to ensure comfort and safety *Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	5	* Puts on chemical resistar	nt boots over feet of suit				
Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners * Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	6	Dons SCBA. Adjusts facep	iece. Does not connect bro	eathing hose. Ope	ens tank		
Puts sleeves of suit over arms and SCBA with the help of assistant. Adjusts for comfortable fit. Dons hard hat , if applicable Raises hood over head carefully. Adjusts for comfortable fit * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve Assistant verifies proper breathing, makes final closure of suit, checks all fasteners * Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	7	Performs negative and pos	itive facepiece seal tests				
fit. Dons hard hat , if applicable 10 Raises hood over head carefully. Adjusts for comfortable fit 11 * Secures all fasteners (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals 12 * Connects breathing hose, opens main valve 13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	8	Puts on inner gloves or sec	ures detachable gloves to	suit			
* Critical Step Failure of this step mandates (leaves room to connect breathing hose) and adjustable leg and head openings and waistband. Reviews emergency hand signals * Connects breathing hose, opens main valve * Connects breathing hose, opens main valve * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	9			lp of assistant. Ad	ljusts for comfortable		
head openings and waistband. Reviews emergency hand signals 12 * Connects breathing hose, opens main valve 13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	10	Raises hood over head car	efully. Adjusts for comforta	able fit			
13 Assistant verifies proper breathing, makes final closure of suit, checks all fasteners 14 Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate	11				djustable leg and		
14 Assistant observes to ensure comfort and safety * Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10	12	* Connects breathing hose,	opens main valve				
* Critical Step Failure of this step mandates Safety is PARAMOUNT Total number steps candidate 10	13	Assistant verifies proper br	eathing, makes final closu	re of suit, checks	all fasteners		
Salety is I AI AI AI AI	14	Assistant observes to ensu	re comfort and safety				
	* Cri			ARAMOUNT		didate	10

Rev. 9/7/18





Hazardous Materials/WMD Technician Level

Ski	II No. HMT-28C	Prim	ary Task:	_	el A Chemical Prontry Personnel)	otectiv	'e
Ob	jective(s): 7.4.2	NFPA Star	ndard: 1072 Editi	2, 2017 on	Candida	ite No.	
		Perform	ance eva	luation she	et		
	FOLLOWING PROCEDURES ASSUSIDERING THE TYPE AND EXTE						
	Procedures if sufficient air	supply is ava	ilable to allo	w appropriate d	ecomtamination befo	ore remo	oval:
Tas	sk					1st	2nd
1	Assistant loosens and remo	oves safety sho	oes or boots	(if applicable)			
2	Assistant opens suit compl	etely and lifts h	nood over hea	ad of wearer			
3	Removes arms, one at a tir between outside surface ar				A, avoiding contact		
4	If possible, sits down and re	emoves legs fr	om suit				
5	Doffs SCBA						
6	Removes inner gloves by r	olling off hand,	inside out				
7	Removes internal clothing	and thoroughly	cleanses bo	dy			
	Procedures if low ai	r alarm has so	ounded with	less than five (5)	minutes of air rema	ining:	
1	Removes disposable clothi	ng					
2	Quickly scrubs and hoses	off, especially a	around the er	trance/exit zipper			
3	Opens zipper enough to all	low access to t	he regulator	and breathing hos	e		
4	Immediately attaches appro	opriate air supp	oly to breathin	ng apparatus			
5	Follow Steps 1 through 7 a	bove					
* C	ritical Step Failure of this st failure on the er		Safety is P	RAMOUNT	Total number steps can must complete to pass		6

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	kill No. HMT-28D			Primary T	ask:	Doffin	g Level "	A" Suit (assistan	t)	
Obje	ective(s): 7.	.4.2	NF	PA Standar	d:	1072, 2017 Edition	7	Candidat	es No.	
				Perfo	rmance e	valuatio	on sheet				
Tas	k									1 st	2 nd
1	Verba	lizes v	whether assistan	t will touch i	nside (clear	n) or outs	side (dirty) p	oart of suit			
2	Unzip	s the s	suit								
3	Remo	ves sı	uit from left arm								
4	Slides	out ri	ght arm								
5	Pulls	suit do	own below the wa	aist							
6	Instru	cts res	sponder to sit								
7	Remo	ves h	ard hat								
8	Pulls I	ooots	off								
9	Pulls	suit of	f from the heel								
10	Instru	cts res	sponder to doff S	CBA							
* Cr	itical St	ер	Failure of this step failure on the entire	mandates e objective	Safety is	PARAN	IOUNT		er steps car lete to pass	ididate	7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	l No. HM	T-28E	Prin	nary Task:	Donning L	evel B	Clothing		
Obje	ective(s):	7.4.2	NFPA S	tandard:	1072, 2017 Edition		Candidates No).	
			Perform	ance eva	aluation sh	neet			
Tas	k							1 st	2 nd
1	Dons Level	'B' suit in a m	anner consister	nt with trainin	g and manufaction	urer's rec	commendation		
2	*Dons glove	s properly (2	sets)						
3	Dons boots								
4	Utilizes tape	as needed							
5	Dons helme	t							
									1
* Cr	itical Step		step mandates entire objective	Safety is P	ARAMOUNT		number steps car complete to pass	ndidate	4

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials/WMD Technician Level

Skill	kill No. HMT-28F Primary Task: Doffing Level 'B' Suit after Decontamination							ı
Obje	ective(s):	7.4.2	NFP	A Standard:	1072, 2017 Edition	Candidat	es No.	
			Perform	ance evalu	ation she	et		
Tasl	k						1 st	2 nd
1	Minimize	cross cont	amination with suit (inside, outside)				
2	Removes	hard hat o	or helmet					
3	* Loosens SCBA harness straps, slides arms out, maintains regulator affixed to facepiece facepiece remains affixed to face							
4	Removes outer gloves							
5	Removes	suit/perso	nal protective equip	ment by rolling o	peeling away	from body		
6	Removes	boots						
7	Pulls suit	away from	heels					
8	Removes	facepiece	from face					
9	Removes	inner glov	es					
10	Documen	ts activity I	og					
* Cri	tical Step		of this step mandates in the entire objective	Safety is PAR	AMOUNT	Total number steps ca must complete to pass		7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29A1	Primary Task:	Fusible N	Metal Plug Leak	Containment - Bu	ılk Ves	sel
Objective(s	3): 7.4.3, 7.4.3	(1)(a) NFPA	Standard:	1072, 2017 Edition	Candidate No.		
		Perfo	rmance ev	valuation she	et		
Task						1 st	2 nd
1. *Ide	ntifies correct rep	air kit					
2. Sele	cts correct tools/p	parts from repa	ir kit				
3. Арр	roaches cylinder	from upwind di	rection				
4. Pos	tions cylinder so	that leak is in g	aseous phase	e, if possible			
5. *Ap _l	oly hood for fusibi	ile plug, or drive	e suitable drift	pin through fusible រុ	olug		
6. *Ass	sures leak has sto	opped (test for I	eak by appro	priate method)			
7. Lea	ves cylinder so th	at leak is in gas	seous phase,	if possible			
8. Hoo	d for fusible plug	- fit yoke with	stud over hea	d of fusible plug			
9. Plac	e gasket against	face of fusibile	plug				
10. Tig	hten stud with wr	rench					
11. Te	st for leaks using	appropriate me	ethod				
12. lns	pects and mainta	ains tools/equip	ment				
13. Co	mpletes required	documentation	for product in	nvolved/actions take	n		
* Critical S	ep Failure of the	nis step mandates ne entire objective	Safety is	PARAMOUNT	Total number steps car must complete to pass	ndidate	10

Rev. 9/7/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL Hazardous Materials Technician





COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	No. HMT-29A2 Primary Task: Fusible Metal of Plug Leak Containi Bulk	nent - No	n-
Obje	ective(s): 7.4.3, 7.4.3(1)(a) NFPA Standard: 1072, 2017 Candidate Edition	No.	
	Performance evaluation sheet		
Tas	k	1 st	2 nd
1	* Identifies correct repair kit		
2	Selects correct tools/parts from repair kit		
3	Approaches cylinder from upwind direction		
4	Positions cylinder so that leak is in gaseous phase, if possible		
5	* Saws off plug flush with valve body; files the surface smooth		
6	* Loosens set screw on clamp assembly, places clamp over plug, places gasket between leaking plug and block on clamp		
7	* Places gasket between leaking plug and clamp block		
8	* Tightens screw enough to stop leak without over tightening		
9	* Assures leak has stopped (tests for leak by using appropriate methods)		
10	Leaves cylinder so that leak is in gaseous phase, if possible		
11	Inspects tools/equipment		
13	Completes documentation for product involved/actions taken		
* Cri	tical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps must complete to p		10

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill 1	Kill No. HMT-29B1 Primary Fusible Plug Threads Leak Containment – Bulk Task: Vessel									
Objec	ctive(s):	7.4.3, 7.4.3(1	I)(b) NFP	A Standard:	1072, 2017 Edition	Candidate No.				
			Perfo	ormance ev	aluation she	et				
Task	(1 st	2 nd		
1 *	Identifies co	orrect repair	kit							
2 5	Selects corre	ect tools/parts	s from repail	r kit						
3 Д	Approaches	cylinder from	n upwind dire	ection						
4 F	Positions cyli	inder so that	leak is in ga	aseous phase, i	f possible					
5 A	Assembles w	rench and a	applies to fus	ible plug						
6 *	Tightens fu	sible plug to	stop leak wi	thout over tight	ening					
7 *	Assures lea	ak has stopp	ed, tests for	leaks by approp	oriate methods					
8 lı	nspects tool	s/equipment								
9 (Completes d	ocumentatio	n for produc	t involved/action	ns taken					
		IF TIG	HTENING F	AILS – OPTIOI	N – HOOD FOR FU	SIBLE PLUGS				
1 L	_eaves cylind	der so that le	eak is in gas	eous phase, if p	oossible					
2 (Cleans arour	nd fusible plu	ıg							
3 F	Places molde	ed gasket on	hood. Fits y	oke with stud c	over head of plug					
4 F	Places hood	with gasket	over yoke aı	nd stud, stud ex	tends out top of ho	od				
5 F	Places gaske	et over stud								
6 8	Screws cap r	nut on stud a	and tightens	gently						
7 T	Tests for leal	ks								
8 If	f plug should	d pull out, dri	ives in suitat	ole drift pin						
* Criti	ical Step		step mandates entire objective		PARAMOUNT	Total number steps cand must complete to pass	didate	11		

Rev. 9/7/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL Hazardous Materials Technician





COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill N	No. F	IMT-29B2	Primary	Task:	Fusible F	Plug Thread	ls Leak	Containment	Non-E	Bulk
Objec	ctive(s):	7.4.3, 7.4.3	3(1)(b)	NFPA SI	tandard:	1072, 2017 Edition		Candidate No.		
			Pe	erform	ance eva	luation s	sheet			
Task									1 st	2 nd
1	* Identi	ies correct re	pair kit							
2	Selects	correct tools/	/parts from	n repair k	xit					
3	Approa	ches cylinder	from upwi	ind						
4	Position	ns cylinder so	that leak	is in gas	eous phase, i	f possible				
5	Assem	oles wrench a	ınd applies	s to fusib	le plug					
6	* Tighte	ens fusible plu	ıg to stop l	eak with	out over tight	ening				
7	* Assur	es leak has st	topped							
8	Leaves	cylinder so th	nat leak is	in gased	ous phase, if p	oossible				
9	Inspect	s tools/equipr	nent							
10	Comple	etes documen	taion for p	roduct ir	nvolved/action	ns taken				
								·		
* Criti	cal Step		this step mar the entire obj		Safety is PA	RAMOUNT		number steps can complete to pass	didate	7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Ski	Skill No.		/IT-29B3	Prin	nary Task:	Fusible Plug	g Blowout -	out – Bulk Vessel		
Obj	ective(s):	7.4.3, 7.4.3(1)(b)	NFF	'A Standard:	1072, 2017 Edi	tion	Candidate	e No.	
			Pe	rfor	mance eva	luation she	eet			
Tas	sk								1 st	2 nd
1	* Identi	fies	correct repair kit							
2	Selects	cor	rect tools/parts from rep	oair kit	approaches c	linder from upw	ind direction			
3	Position	ns cy	ylinder so that leak is in	the ga	seous phase,	f possible				
4	* Drive:	s sui	table drift pin into valve	openi	ng					
5	5 Assures leak has stopped (tests for leak by appropriate methods)									
6	Inspect	ts too	ols/equipment							
7	Comple	etes	documentation for prod	luct inv	olved/actions t	aken				
* C	Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candidate must complete to pass								5	

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	Skill No. HMT-29C1 Primary Task: Cylinder Sidewall Leak Containm (Horizontal Position) – Bulk Vess								
Obje	ective(s): 7.4.3, 7.4.3(1)	(c) NFPA S	tandard:	1072, 2017 Edition	Candidate No.				
		Perform	nance eva	aluation she	eet				
Tas	k					1 st	2 nd		
1	* Identifies correct repair	kit							
2	Selects correct tools/part	s from repair ki	t						
3	Approaches cylinder from	n upwind directi	ion						
4	Positions cylinder so that	leak is on the	top						
5	Chocks container to prev	ent rolling							
6	Slips one end of the chair	n under the cyl	inder, pulls th	nrough enough cha	ain to reach leak				
7	Places yoke screw in pat	ch depression							
8	Attaches ends of chain to	each side of y	oke keeping	chains as short as	s possible and straight				
9	Cleans area of leak, plac	es gasket and	patch over le	ak					
10	* Tightens cap screw end	ough to stop lea	ak without ov	ertightening					
11	* Assures leak has stopp	ed (tests for lea	ak by approp	riate method)					
12	Leaves cylinder so that le	eak is in gaseou	us phase, if p	ossible					
13	Inspects tools/equipment	:							
14	Completes documentatio	n for product in	volved/action	ns taken					
* Cri	itical Step Failure of this stallure on the e		Safety is P	ARAMOUNT	Total number steps cand must complete to pass	lidate	10		

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill N	o. H	IMT-29C2	Prin	nary Task:	Cylinder Sid	dewall Leak Conta essel	ıinmen	it -
Object	tive(s):	7.4.3, 7.4.3(1)(c)	NFPA S	tandard:	1072, 2017 Edition	Candidate No.		
			Perform	nance eva	luation she	et		
Task							1 st	2 nd
1	* Identif	ies correct repair k	it					
2	Selects	correct tools/parts	from repair l	kit				
3	Approa	ches cylinder from	upwind direc	tion				
4	Position	ns cylinder so that le	eak is on the	top				
5	Slips or	ne end of the chain	under the cy	rlinder, pulls t	hrough enough ch	ain to reach leak		
6	Cleans	area of leak, places	s gasket ove	r leak				
7	Places	yoke screw in patcl	n depression	ı				
8	Attache	s ends of chain to	each side of	yoke keeping	chains as short as	s possible		
9	Insures	chain is straight, n	ot twisted					
10	* Tighte	ns cap screw enou	gh to stop le	ak without ov	er tightening			
11	* Assur	es leak has stoppe	d (test for lea	ak by appropr	iate methods)			
12	Leaves	cylinder so that lea	ık is in gased	ous phase, if p	possible			
13	Inspect	s tools/equipment						
14	Comple	tes documentation	for product i	nvolved/actio	ns taken			
* Critic	al Step	Failure of this step failure on the entite	o mandates re objective	Safety is P	ARAMOUNT	Total number steps can must complete to pass	didate	10

Rev. 9/7/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL Hazardous Materials Technician





COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	No. HMT-29D1	Prima	ry Task:	Valve B	lowou	ıt Leak Containme	ent			
				Non-Bu	lk Ves	ssel				
Obje	ective(s): 7.4.3, 7.4.3(1)(d)	NFPA Sta	ndard:	1072, 2017 Edition		Candidate No.				
	I	Performa	nce eva	luation	sheet					
Tas	k						1 st	2 nd		
1	* Identifies correct repair kit									
2	Selects correct tools/parts fro	m repair kit								
3	Approaches cylinder from up	wind direction	n							
4	Positions cylinder so that leak is in gaseous phase, if possible									
5	* Drives large drift pin into valve opening									
6	Removes outlet cap from vent valve on hood and opens valve									
7	Assembles base assembles v	with spacer a	ind ramp							
8	Rolls cylinder upright onto ba	se assembly								
9	Cleans shoulder of cylinder, p	olaces gaske	t on hood, ¡	places assem	bly ove	er valve				
10	Places yoke on hood, attache	es chain to yo	oke, turns d	liamond links	in chai	n to the short position				
11	Hand tightens yoke screws e	qually								
12	* Closes vent valve on hood									
13	Replaces outlet cap on vent	valve and tigh	ntens							
14	* Assures leak has stopped									
15	5 Leaves cylinder in position so that leak remains in gaseous phase, if possible									
16	Inspects tools/equipment									
17	Completes documnetation for	r product invo	olved/action	ns taken						
* Cr	Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candidate must complete to pass									

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	kill No. HMT-29D2			D2	Pri Ta:	mary sk:	Valve E Vessel	Blowout (due to	stripped threads) – No	า-Bu	ılk
Obje	ective(s): 7	7.4.3,	7.4.3(1)	(d)	NFPA S	Standard:	1072, 2017 Edition	Candidate No.		
					I	Perfor	mance e	valuation she	eet		
Task	<									1 st	2 nd
1	* Ident	fies co	orrect	repair kit							
2	Selects	corre	ct too	ls/parts fr	om r	epair kit					
3	Approa	iches (cylinde	er from u	pwind	d direction					
4	Positio	ns cyli	inder s	so that lea	ak is	in gaseous	s phase, if po	ossible			
5	* Drive	s suita	able dr	ift pin into	o valv	ve opening	g (if pin fails-	option- to attach hood;	saws pin)		
6	Applies	hood	asser	mbly – re	move	es outlet ca	ap from vent	on hood and opens va	lve		
7	Assem	bles b	ase as	ssembly \	with s	spacer and	I ramp and s	ecures			
8	Rolls u	pright	cylind	er onto b	ase a	assembly					
9	Cleans	shoul	der of	cylinder,	plac	es molded	I gasket on h	ood, and places assen	nbly over valve		
10	Adjusts	cap s	screws	s in yoke	so th	at points o	of screw exte	nd only slightly below y	/oke		
11	Places yoke	yoke	on hoo	od with so	crews	s positione	d in dimples	, insure chains are stra	ight, hooks chains over ears of		
12	* Hand	tighte	ns yol	ke screws	s equ	ıally; uses	wrench to tig	ghten hood			
13	Closes	vent v	valve o	on hood							
14	* Repla	ices o	utlet c	ap on ve	nt an	d tightens					
15	Assure	s leak	has s	topped (t	ests	for leak by	appropriate	method)			
16 Leaves cylinder in position so that leak remains in gaseous phase, if possible											
17	Compl	etes d	ocume	entation for	or pro	oduct invol	ved/actions	taken			
* Cri	ritical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candidate must complete to pass									2	

Rev. 9/7/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL Hazardous Materials Technician





COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill N	No. HM 7	Г-29D3	Primary T	ask:		owout Leak C Stripped Threa	ontainment – Bull ads)	k Vess	el
Objec	ctive(s): 7	7.4.3, 7.4.3	3(1)(d)	NFPA	Standard:	1072, 2017 Edition	Candidate I	No.	
			Per	forma	nce eval	uation she	et		
Task								1 st	2 nd
1	*Identifies	correct rep	oair kit						
2	Selects corr	ect tools/p	parts from re	pair kit	, approaches	cylinder from up	wind direction		
3	Positions cy	linder so	that leak is i	n the ga	aseous phase	e, if possible			
4	* Drives su	itable drift	pin into valv	/e open	ing				
		IF DR	RIFT PIN FA	AILS –	OPTION – I	HOOD AND BA	R ASSEMBLY		
1	Rolls cylind up	er so that	valves are i	n vertic	al position re	lative to each oth	er with leaking valve		
2	Removes o	utlet cap	from vent va	lve on h	nood and ope	ens valve			
3			crews and re me of contai		ack screws er	nough to allow ins	sertion of bar		
4	Cleans area	a around v	valve, places	s molde	d gasket on l	nood, places asso	embly over valve		
5	Adjusts jac	k screws t	to ensure tha	at cap s	crew is over	hood and bar fits	tightly inside chime		
6	* Tightens	cap screw	over hood e	enough	to stop leak	without overtighte	ening		
7	* Closes ve	nt valve o	n hood						
8	Replaces o	utlet cap	on vent valv	e and ti	ghtens				
9	* Assures le	eak has st	topped, tests	s for lea	ks by approp	riate method			
10	Leaves cyli	nder in po	osition so tha	it leak r	emains in a g	gaseous phase, if	possible		
11	Inspects to	ols/equipn	nent						
12	Completes	documen	tation for pro	duct in	volved/action	s taken			
* Criti	cal Step		his step manda he entire object		Safety is PA	RAMOUNT	Total number steps can must complete to pass	ıdidate	9

Rev. 9/7/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL Hazardous Materials Technician





COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29E1	Primary Task:	Valve Gl	and Stem Leak	Containment – B	Bulk Ve	ssel				
Objective(s	7.4.3, 7.4.3((1)(e) NFPA \$	Standard:	1072, 2017 Edition	Candidate No.						
		Perfor	mance eva	luation she	et						
Task						1 st	2 nd				
1. * Ide	ntifies correct repa	air kit									
2. Sele	cts correct tools/p	arts from repair	kit, approach	es cylinder from th	e upwind direction						
3. Posit	ions cylinder so th	hat leak is in ga	seous phase,	if possible							
4. Appl											
5. * Tig											
6. * Ass											
7. Leav	es cylinder so tha	nt leak is in gaso	ous phase, if p	ossible							
	II	F TIGHTENING	FAILS - OP	TION – HOOD AS	SEMBLY						
1. Rem	ove outlet cap from	m vent valve or	n hood and op	en valve							
2. Loos	ens adjusting scre	ews, retract jac	k screws and i	nserts adjustable t	oar assembly						
3. Clea	ns around leaking	ງ valve, places ເ	molded gaske	on hood							
4. Place	es hood over leak	ing valve and ti	ghtens adjusta	able bar assembly							
5. Tight	ens enough to sto	op leak, closes	vent valve on	hood							
6. * Ass	sures leak has sto	pped, tests lea	k by appropra	e methods							
7. Inspe	ects tools/equipme	ent									
8. Com	pletes documenta	ation for produc	involved/action	ons taken							
* Critical Sto	Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps canomust complete to pass										

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29E2	Primary Ta	····	Ive Gland St on – Bulk Ves	em Packing Leak (Contain	ment
Objective(s	s): 7.4.3, 7.4.3(1)(e)	NFPA Standa		72, 2017 ition	Candidate No.		
		Performanc	e evalu	ation she	et		
Task						1 st	2 nd
1. * Ide	ntifies correct repair kit						
2. Sele	cts correct tools/parts from	n repair kit and app	roaches cylir	nder from upwin	d direction		
3. Posi	tions cylinder so the leak	is in gaseous phase	e, if possible				
4. * Ap _l	olies wrench to correct pa	cking nut and tighte	ens to stop le	ak without over	tightening		
5. * Ass	sures leak has stopped, te	ests for leak by app	ropriate meth	nod			
6. Leav	es cylinder so that leak is	in gaseous phase	, if possible				
	IF T	IGHTENING FAI	LS – APPL	Y HOOD ASS	EMBLY		
1. Rem	oves outlet cap from vent	valve on hood and	l opens valve				
2. Asse	embles base assembly wit	h spacer and ramp	and secures	;			
3. Rolls	upright cylinder onto bas	e assembly					
4. Clea	ns shoulder of cylinder. P	laces molded gask	et on hood a	nd places assem	nbly over valve		
5. Adju	sts cap screws in yoke sc	that points of scre	w extends on	ly slightly below	yoke		
	es yoke on hood with scre of yoke	ews positioned in di	imple, insure	s chains are stra	ight, hook chains over		
7. Hand	d tightens yoke screws ed	ually and uses wre	nch to tighter	n hood			
8. * Clo	ses vent on hood						
9. Repl	aces outlet cap on vent v	alve and tightens					
10. * As	ssures leak has stopped,	tests for leak by ap	propriate me	thod			
11. Lea	ves cylinder in position s	that leak remains	in gas phase	e, if possible			
12. Ins _l	pects tools/equipment						
13. Cor	mpletes documentation fo	r products involved	/actions take	n			
* Critical S	tep Failure of this step failure on the entire		ty is PAR	TNUOMA	Total number steps car must complete to pass	ndidate	12

Rev. 9/7/18





Hazardous Materials Technician



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HMT-29E3 Primary Task: Valve Stem Packing/Gland Leak Containment Vessel	nt – Bulk	
Objective(s): 7.4.3, 7.4.3(1)(e) NFPA Standard: 1072, 2017 Candida Edition	te No.	
Performance evaluation sheet		
Task	1 st	2 nd
1. * Idenifies correct repair kit		
2. Selects correct tools/parts from repair kit, approaches cylinder from the upwind direction		
3. Positions cylinder so that leak is in gaseous phase, if possible		
4. Ensures valve stem is closed		
5. Applies wrench to tighten packing nut		
6. * Tightens to stop leak without over tighting		
7. * Assures leak has stopped, tests leak by appropriate methods		
8. Leaves cylinder so that leak is in gasous phase, if possible		
IF TIGHTENING FAILS – OPTION – HOOD ASSEMBLY		
Remove outlet cap from vent valve on hood and opens valve		
2. Loosens adjusting screws, retracts jack screws and inserts adjustable bar assembly		
3. Cleans around leaking valve, places molded gasket on hood		
4. Places hood over leaking valve and tightens adjustable bar assembly		
5. Tightens enough to stop leak, closes vent valve on hood		
6. * Assures leak has stopped, tests leak by approprate methods		
7. Inspects tools/equipment		
8. copletes documentation for product involved/actions taken		
* Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps must complete to page		12

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	·29F′	1	Prim Task	-	Valve Ir	nlet Thread I	Leak	Containment - E	Bulk Ve	ssel	
Objective(s): 7.4	1.3, 7.	.4.3(1)	(f)	NFPA S	tandard:	1072, 2017 Edition		Candidate No.		
				F	erform	nance ev	aluation	she	et		
Task										1 st	2 nd
1. * Ide	ntifies c	orrec	t repa	ir kit							
2. Sele	cts corr	ect to	ols/pa	rts fro	om repair	kit, approac	hes cylinder fro	om the	e upwind direction		
3. Posi	tions cy	linder	so th	at is i	n gaseous	s phase, if p	ossible				
4. * Ap	plies wr	ench [·]	to val	/e bo	dy						
5. * Tig	htens v	alve s	lowly	into c	cylinder w	ithout over t	ighting				
6. * As	6. * Assures leak has stopped, test leak by appropriate methods										
7. Leav	es cylir	ıder s	o that	leak	is in gaso	us phase, if	possible				
			IF	TIGI	HTENING	FAILS - O	PTION – HOOE	O ASS	SEMBLY		
1. Rem	ioves ot	ıtlet c	ap fro	m vei	nt valve o	n hood and	opens valve				
2. Loos	sens adj	ustino	gscre	ws, re	etracts jac	k screws ar	nd inserts adjus	table	bar assembly		
3. Clea	ns arou	nd lea	aking	valve	, places m	nolded gask	et on hood				
4. Plac	es hood	l over	leakir	ng va	lve and tig	ghtens adjus	stable bar asser	mbly			
5. Tigh	tens en	ough [.]	to sto	o leak	k, closes v	ent valve o	n hood				
6. * As	6. * Assures leak has stopped, tests leak by approprate methods										
7. Insp	ects too	ls/equ	uipme	nt							
8. Com	pletes	nuook	nentat	ion fo	or product	involved/ac	tions taken				
* Critical St	8. Completes documentation for product involved/actions taken Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candidate must complete to pass										

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	НМ	T-29F2	Primary Task:	Valve Inlet	Гhread Leak Cor	ntainment Non – Bu	ılk Ves	sel	
Objective(s):	7.4.3, 7.4.3	(1)(f) NFPA	Standard:	1072, 2017 Edition	Candidate No.			
Performance evaluation sheet									
Task							1 st	2 nd	
1. * Ident	ifies c	orrect repair ki	t						
2. Select	s corre	ect tools/parts t	from repair kit						
3. Approa	aches	cylinder from ι	pwind direction						
4. Positio	ns cyl	inder so that le	eak is in gaseous pl	nase, if possible					
5. * Appli	es wre	ench to valve b	ody, tightens valve	slowly into cylinde	er without over tightening	g			
6. * Assu	res lea	ak has stopped	I (tests for leak by a	ppropriate method	ds)				
7. * Leav	es cyli	nder so that le	ak is in gasous pha	se, if possible					
			IF TIGHTENING	3 FAILS – OPTIO	N - APPLY HOOD ASS	SEMBLY			
1. Remov	ves ou	tlet cap from v	ent on hood and op	ens valve					
Assembles base assembly with spacer and ramp and secures									
3. Rolls o	ylinde	r upright onto l	base assembly						
4. Cleans	s shou	lder of cylinder	, places gasket on	hood and places a	assembly over valve, ad	ljust cap screw in yoke			
5. Places yoke	yoke	on hood with s	screws positioned in	dimples,insures o	chains are straight, hool	ks chains over ears of			
6. Hand t	tighten	s yoke screws	equally, uses wren	ch to tighten hood	ľ				
7. * Close	es ven	t valve on hoo	d						
8. Replac	ces ou	tlet cap on ven	t valve and tightens	3					
9. * Assu	9. * Assures leak has stopped (tests for leak by appropriate methods)								
10. Leaves cylinder in position so that leak remains in a gaseous phase, if possible									
11. Inspe	11. Inspects tools/equipment								
12 Comp	12 Completes documentation for product involved/actions taken								
* Critical St	ер		is step mandates e entire objective	Safety is P	ARAMOUNT	Total number steps can must complete to pass	didate	12	

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29G1	Primary Tas			ontainment – Bul mpletely Close)	k Vess	el
Objective(s): 7.4.3, 7.4.3(1)(g) NFPA S	tandard:	1072, 2017 Edition	Candidate No.		
		Perform	nance ev	aluation she	et		
Task						1 st	2 nd
1. Appro	paches cylinder from th	e upwind direction					
2. Posit	ons cylinder so that lea	ak is in the gaseous	phase, if possi	ble			
3. Disco	nnects from a process,	, reconnect					
4. *Gen	ly opens and closes th	e valve to clear the	seat				
5. Disco	nnects and applies out	let cap and gasket					
6. *Assı	6. *Assures that leak has stopped, tests by appropriate methods						
7. Leave	es cylinder in a position	so that leak remain	s in a gasous p	phase, if possible			
		IF TIGHTENII	NG FAILS – O	PTION – HOOD ASSEM	BLY		
1. Remo	oves outlet cap from ve	nt valve on hood and	d opens valve				
2. Loos	Loosens adjusting screws, retracts jack screws and inserts adjustable bar assembly						
3. Clear	s around leaking valve	e, places molded gas	ket on hood				
4. Place	s hood over leaking va	live and tightens adj	ustable bar ass	sembly			
5. Tight	ens enough to stop leal	k, closes vent valve	on hood				
6. Assures leak has stopped, tests leak by approprate methods							
7. Inspects tools/equipment							
8. Com	Completes documentation for product involved/actions taken						
9. Inspects tools/equipment							
10. Completes documentation for product involved/actions taken							
* Critical S		s step mandates e entire objective	Safety is	PARAMOUNT	Total number steps car must complete to pass	didate	12

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	kill No. HMT-29G2 Primary Task: Valve Seat Leak Containn (valve will not completely					Bulk	
Objective(s): 7.4.3, 7.4.3(1)(g)	NFPA S	tandard:	1072, 2017 Edition	Candidate No.		
Performance evaluation sheet							
Task						1 st	2 nd
1. Approaches cylinder from the upwind direction							
2. Positions cylinder so that the leak is in the gaseous phase, if possible							
3. If disc	onnected from the process, re	econnects					
4. *Gentl	y opens and closes the valve	to clear the s	eat				
5. Discor	nnects and applies outlet cap	and gasket					
6. *Assures that the leak has stopped (tests for leak by appropriate method)							
7. Leaves cylinder in a position so that leak remains in gaseous phase, if possible							
	IF CAP AND G	ASKET FAIL	OPTION - AF	PPLY HOOD ASSEME	BLY		
1. Remo	ves outlet cap from vent valve	e on hood and	l opens valve				
2. Assen	nbles base assembly with spa	acer and ramp	and secures				
3. Rolls o	cylinder upright onto base ass	sembly					
4. Cleans	s shoulder of cylinder, places	molded gask	et on hood, place	es assembly over valve	e, adjust screws in yoke		
5. Places	s yoke on hood with screws p	ositioned in d	imple, insures ch	ains are straight, hook	s chains over ears of yoke		
6. Hand	tightens yoke screws equally	uses wrench	to tighten hood				
7. Closes	s vent valve on hood						
8. Repla	ces outlet cap on vent valve a	and tightens					
9. *Assures leak has stopped (tests for leak by appropriate method)							
10. Leaves cylinder in position so that leak remains in the gaseous phase, if possible							
11. Inspects tools/equipment							
12. Completes documentation for product involved/actions taken							
* Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps can must complete to pass							14

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	No. HMT-29H1 Primary Task: Valve Stem Assembly Blowout Le Containment - Bulk Vessel							
Objective(s): 7.4.3, 7.4.3(1)(h)	NFPA Standard:	1072, 2017 Edition	Candidate No.				
		Performance e	evaluation she	et				
Task				1	st 2 nd			
1. * Ide	ntifies correct repair kit							
2. Sele	2. Selects correct tools/parts from repair kit, approaches cylinder from upwind direction							
3. Posi	ions cylinder so that le	ak is in the gaseous	phase, if possible					
4. * Dri	ves suitable drift pin int	o valve opening						
	IF DRIFT PIN FAILS – OPTION – HOOD AND BAR ASSEMBLY							
1. Rem	oves outlet cap from ve	ent valve on hood an	d opens valve					
	ens adjusting screws a embly behind chime of o		ws enough to allow in	sertion of bar				
3. Clea	ns area around valve, p	olaces molded gaske	et on hood, places ass	embly over valve				
4. Adju	sts jack screws to ensu	re that cap screw is	over hood and bar fits	tightly inside chime				
5. * Tig	htens cap screw over h	ood enough to stop	leak without over tight	ening				
6. * Clo	ses vent valve on hood	I						
7. Repl	aces outlet cap on ven	valve and tightens						
8. * Ass	sures leak has stopped	, tests leaks by appro	opriate method					
9. Leaves cylinder in position so that leak remains in a gaseous phase, if possible								
10. Inspects tools/equipment								
11. Cor	11. Completes documentation for product involved/actions taken							
* Critical Sto	Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candidate must complete to pass							

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29H2	Primary Task:		m Assembly Blowout/Leak ent, Non-Bulk Vessel				
Objective(s)	: 7.4.3, 7.4.3(1)(h)	NFPA Standard:	1072, 2017 Edition	Candidate N				
Performance evaluation sheet								
Task					1 st 2 nd			
1. * Identif								
2. Selects	correct tools/parts from re	epair kit						
3. Approa	ches cylinder from upwind	direction						
Positions cylinder so that leak is in gaseous phase, if possible								
5. * Drives	small drift pin into the val	ve body						
6. Moves	cylinder to isolated area							
7. Leaves	cylinder so that leak is in	gasous phase, if pos	sible					
8. Inspects	s tools/equipment							
9. Comple	tes documentation for pro	duct involved/actions	taken					
				'	l			
* Critical Step Failure of this step mandates failure on the entire objective Safety is PARAMOUNT Total number steps candid must complete to pass								

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-29H3	Primary Task	Valve E	Broken Off/Lea	k Containment – I	3ulk V	essel	
Objective(s)): 7.4.3, 7.4.3(1)(h) NFPA S	tandard:	1072, 2017 Edition	Candidate No.			
Performance evaluation sheet								
Task						1 st	2 nd	
1. * Ident	ifies correct repair kit							
2. Selects	s correct tools/parts fro	m repair kit						
3. Approa	aches cylinder from upv	wind direction						
4. Positio	ns cylinder so that leak	is in gaseous pha	se, if possible					
5. * Drive	s suitable drift pin into	the valve body						
6. * Assu	res leak has stopped (t	ests for leaks by ap	proprate method	ds)				
	IF DRI	FT PIN FAILS - O	PTION – HOOD	AND BAR ASSEMBLY	·			
1. Rolls c	ylinder so that valves a	are in vertical position	on relative to eac	ch other with leaking va	lve up, if applicable			
2. Remov	ves outlet cap from ven	t valve on hood and	d opens valve					
3. Looser conta		d retracts jack scre	ws enough to allo	ow insertion of bar asse	embly behind chime of			
4. Cleans	area around valve, pla	aces molded gaske	t on hood, places	s assembly over valve				
5. Adjusts	s jack screws to ensure	e that cap screw is	over hood and ba	ar fits tightly inside chim	ne			
6. * Tight	ens cap screw over ho	od enough to stop I	eak without over	tightening				
7. * Close	es vent valve on hood							
8. Replac	ces outlet cap on vent v	alve and tightens						
9. * Assu	9. * Assures leak has stopped							
10. Leaves cylinder in position so that leak remains in gaseous phase, if possible								
11. Inspe	11. Inspects tools/equipment							
12. Comp	12. Completes documentation for product involved/actions taken							
* Critical Ste		step mandates entire objective	Safety is P	ARAMOUNT	Total number steps can must complete to pass	didate	11	

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HMT-29H4	Primary Task:		Blowout or Broken C at – Non-Bulk Vessel	Off L	eak
Objective(s): 7.4.3, 6.4.3(1)(h)	NFPA Standard:	1072, 2017 Edition	Candidate No.		
Pe	erformance eva	luation she	et		
Task				1 st	2 nd
1. *Identifies correct repair kit					
2. Selects correct tools/parts from repair	kit				
3. Approaches cylinder from upwind direct	ction				
4. Positions cylinder so that leak is in gas	seous phase, if possible				
5.*Drives suitable drift pin into valve oper	ning (if pin fails-option-to at	tach hood; saws pin)			
6. Applies hood assembly – removes out	tlet cap from vent on hood a	nd opens valve			
7. Assembles base assembly with space	r and ramp and secures				
Rolls cylinder upright onto base asser	nbly				
9. Cleans shoulder of cylinder, places mo	olded gasket on hood, and p	laces assembly over v	valve		
10. Adjusts cap screws in yoke so that po	oints of screw extend only sl	lightly below yoke			
11. Places yoke on hood with screws pos	sitioned in dimples, insure c	hains are sraight, hool	c chains over ears of yoke		
12. Hand tightens yoke screws equally,	and uses wrench to tighten	hood			
13. *Closes vent valve on hood					
14. Replaces outlet cap on vent and tight	tens				
15. *Assures leak has stopped (tests for	leak by appropriate method)			
16. Leaves cylinder in position so that lea	ak remains in gaseous phas	e, if possible			
17. Inspects tools/equipment					
18 Completes documentation for product	t involved/actions taken				
* Critical Step Failure of this step mar failure on the entire obj		RAMOUNT	Total number steps candidate must complete to pass	te	13

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	No. H	MT-30A	Primary Task:	Close Open	Valves on	a Pressure Cont	ainer	
Objec	ctive(s):	7.4.3, 7.4.3	(2)(a)	NFPA Standard:	1072, 2017 Editio	Candidat on	e No.	
			Perfo	rmance evaluati	on sheet			
T 1							4 .	
Task							1 st	2 nd
1	* Identifi	es correct re	epair kit					
2	Selects	correct tools	/parts from repair k	kit				
3	Approac	hes containe	er from upwind dire	ection				
4	Position	s cylinder so	that leak is in a ga	as phase, if possible)			
5	* Closes	valve with a	appropriate tool(s)					
6	* Assure	es leak has s	stopped (test for lea	ak by appropriate m	ethod)			
7	Leaves	container in	position so that lea	ık remains in gas pl	nase, if poss	sible		
8	Deconta	minates tool	ls and equipment					
9	Inspects	tools and e	quipment					
10	Docume	ents product	control operations					
* Criti	cal Step		this step mandates the entire objective	Safety is PARA	MOUNT	Total number steps car must complete to pass	ndidate	7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-30B	Primary Task:	Replace M	lissing Plugs	on a Pressure Co	ontaine	: r
Objective(s): 7.4.3, 7.4	.3(2)(b) NFI	PA Standard:	1072, 2017 Edition	Candidat	e No.	
		Perform	mance eval	uation she	eet		
Task:						1 st	2 nd
1. *Ider	ntifies correct re	epair kit					
2. Sele	cts correct tool	s/parts from repair	kit				
3. Posi	ions container	so the leak is in ga	asous phase, if	possible			
4. Clos	e plug opening	with appropriate p	olug or drive sui	table drift pin into	o opening.		
5. * As:	sures leak has	stopped (test for le	eak by appropria	ate method)			
6. Leav	es container ir	n position so that le	ak remains in g	as phase			
7. Deco	ntaminates tools	and equipment					
8. Inspe	cts tools and eq	uipment					
9. Doci	ıments produc	t control operations	5				
* Critical St		f this step mandates the entire objective	Safety is PA	RAMOUNT	Total number steps can must complete to pass	didate	7

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	No. HN	IT-30C	Primary Ta	ısk: Tigl	nten Loose	Plugs on a Pressu	ire Conta	ainer
Obje	ective(s):	7.4.3, 7.4.3(2)(c)	NFP	'A Standard:	1072, 2017 Edition	Cand	idate No.	
			Perform	ance eva	aluation s	sheet		
Tasl	k:						1 st	2 nd
1	* Identifies	correct repair kit						
2	Selects co	rrect tools/parts fi	om repair ki	t				
3	Approache	s container from	upwind dired	ction				
4	Positions of	container so the le	eak is in gas	ous phase, if	possible			
5	Assembles	wrench and app	lies to conta	iner plug				
6	* Tightens	fusible plug to sto	op leak witho	out over tight	ening			
7	* Assures	eak has stopped	(test for leal	k by appropri	ate method)			
8	Leaves co	ntainer in position	so that leak	remains in (gas phase			
9.	Decontamin	ates tools and equi	pment					
10.	Inspects too	ols and equipment						
11.	Documents	product control ope	erations					
* Cri	itical Step	Failure of this step failure on the entir		Safety is P	ARAMOUNT	Total number steps must complete to pa		8

Rev. 9/7/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	НМТ	Г-31	Primary Task:	_		Nail/Forklif – 55 Gallor	t Puncture L n Drum	.eak	
Objective(s	5): 7	7.4.3, 7.4.3 (3)(a-d)	NFPA S	tandard:		72, 2017 lition	Candidate No		
		Per	formanc	e evalua	tion	sheet			
Task								1 st	2 nd
1. *Sele	ects a	nd uses proper PPE							
		opropriate plug/patch n ility, etc	naterials an	d tools to co	ntrol le	eak based on	size,		
3. Appr	roache	es container from the up	phill/upwind	d side, if poss	sible				
4. Avoi	ds ste	pping in or exposing se	elf to produc	ct(s), if possi	ble				
5. Posi	tions o	drum to temporarily stop	p leak, if po	ssible					
6. Appl	lies se	lected plug/patch to sto	p the leak	without incre	asing _l	problem			
7. Ove	rpacks	drum, if necessary							
8. Mark	ks and	labels overpack conta	iner						
* Critical St	ер	Failure of this step mandat failure on the entire objecti		ty is RAMOUNT	Г	Total number s	steps candidate	must	4

Rev. 9/10/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HN	/IT-32	Prir	nary Tasl	c :	Slide-in O	ver-pa	ck – 55 Gallon [Orum	
Objective(s	s) :	7.4.3, 7.4.3(3	3)(a)(b)	NFPA S	tandard:	1072, 20 Edition	17	Candidate N	lo.	
			Pe	rforma	nce eva	luation	shee	t		
Task									1 st	2 nd
1. * Se	lects	appropriate o	ver-pacl	k drum						
2. App	roac	hes problem c	ontainer	from the	uphill/upwi	nd side, if po	ossible			
3. Ren	nove	s the lid from t	he over-	pack drun	n					
4. * Po	sitio	ns over-pack o	drum at b	oottom of	problem c	ontainer at a	45 degr	ree angle		
5. Slid	es pr	oblem contain	ner into tl	he over-pa	ack drum					
6. Star	nds c	ver-pack drun	n upright	İ						
7. * Ins	stalls	over-pack dru	ım's cov	er and tigl	ntens					
8. Dec	onta	minates/inspe	cts/main	tains tools	3					
9. Con	nplet	es documenta	tion of p	roduct cor	ntrol activit	es				
10. * C	omp	letes the evolu	ution as	directed b	y the exan	niner				
* Critical S	tep	Failure of this failure on the			Safety is	PARAMO	UNT	Total number steps of must complete to pa		6

Rev. 9/10/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No.	HMT-33	Prim	ary Task:	Slip-over O	ver-pack – 55 (Gallon Dr	um
Objective(s	s): 7.4.3, 7.4.3(3)(b)	NFPA St	andard:	472	Candidates	s No.	
	:	Perform	ance eva	luation she	et		
Task						1 st	2 nd
1. * Se	lects appropriate over-p	ack drum					
2. App	roaches problem contai	ner from the	e uphill/upwir	nd side, if possible			
3. Ren	noves the lid from the ov	er-pack dru	ım				
4. * Po	sitions over-pack drum	over proble	m container				
5. Star	nds over-pack drum upri	ght with pro	blem contair	ner enclosed			
6. * Ins	stalls over-pack drum co	ver and tigl	ntens				
7. Dec	ontaminates, inspects, r	maintains to	ols and equi	pment			
8. Con	npletes documentation o	of product c	ontrol activiti	es			
9. * Co	empletes the evolution a	s directed b	y the examir	ner			
* Critical S	tep Failure of this step r		Safety is PA	ARAMOUNT	Total number steps		5

10/14 (SS Rev 1/10/14)



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HM	T-34 Primary Ta	sk: Liquid Produ	ct Transfer			
Objective(s): 7	7.4.3, 7.4.3(4)	NFPA Standard:	1072, 2017 Edition	Candidat	e No.	
		Performance evalu	uation sheet			
Task:					1 st	2 nd
	ppropriate Personal Furer's recommendation	Protecting Equipment con.	onsistent with training	and		
2. Identifies	compatible recovery	container and transfer e	quipment.			
3. Monitors f	or hazards.					
4. Properly b	oonds and grounds co	ontainers.				
5. Transfers	liquid from leaking co	ontainer into recovery co	ontainer.			
6. Suppress	es vapors.					
7. Decontarr	ninates, inspects, and	maintains tools and eq	uipment.			
8. Complete	s documentation for p	oroduct control operation	ns			
* Critical Step	Failure of this step mand failure on the entire object			number steps car complete to pass	ndidate	6

Rev 9/10/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HM	Γ-35 Primary Task:	Grounding Pro	cedures - l	Product Transfer	Opera	tion
Objective(s): 7.	4.4.1, 7.4.4.1(B) NI	FPA Standard:	472, 2013 Edition	Candidat	e No.	
	Per	formance evalua	ation sheet			
Task:					1 st	2 nd
1. *Demonsti	rates ability to set up and o	operate mass decor	ntamination eq	uipment		
2. Demonstra	ates crowd management to	echniques				
3. Determine	s effectivness of mass ded	contamniation opera	ations.			
4. Documen	ts mass deconamination a	activities per AHJ po	licies			
* Critical Step	Failure of this step mandates failure on the entire objective	Safety is PAR	MOUNT	Total number steps car	didate	3

Rev. 9/10/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HM	T-36 Primary Task:	Grounding Pro	cedures - I	Product Transfer	Opera	tion
Objective(s): 7.	.4.4.2, 7.4.4.2(B)	NFPA Standard:	1072, 2017 Edition	Candidat	e No.	
	Pe	erformance evalua	tion sheet			
Task:					1 st	2 nd
1. Selects ted	chnical decontamination	procedure to minimize	e hazard			
2. *Sets up a	nd implements technical	decontamination ope	rations			
3. Evaluates	effectiveness of technical	al decontamination pro	ocess			
4. Completes	s required documentation	of technical deconta	mination oper	ations		
* Critical Step	Failure of this step mandates failure on the entire objective		MOUNT	Total number steps car	ndidate	3

Rev. 9/10/18



COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill	No.	HM	T-37	Primary Task	(: E	valuating ar	nd Reporting	Progress			
Obje	ective(s): 7	.5.1, 7.5	5.1(B)	NFP	A Standard:	1072, 2017 Edition	,	Candidat	e No.	
				!	Perfo	rmance eval	uation sheet				
Tas	k:									1 st	2 nd
1.	Identi	ies in	cident a	ction plan obje	ctives	for controlling f	unctions at the i	ncident			
2.	Identi	ies in	cident a	ıction plan obje	ctives	for decontamin	ation procedure	s at the incide	ent		
3.	* Eval plan	uates	the effe	ectiveness of ar	ny con	trolling function	s identified in th	e incident act	ion		
4.	•		the effe	ctiveness of an	y deco	ontamination pro	ocedures identif	ied in the inci	dent		
5.	Recor	nmen	ds impr	ovements or ch	nanges	s to product con	trolling functions	s as needed			
6.	Recor	nmen	ds impr	ovements or ch	nanges	to decontamin	ation procedure	as needed			
* Cri	itical St	ер		of this step manda		Safety is PAR	RAMOUNT	Total number	•	didate	4

10/14 (SS Rev 1/10/14)



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No	o. HMA-38A Primary Ta	ısk:	Assisting in the l	Debriefing		
Object	tive(s): 7.6.1(B)		NFPA Standard: 1072, 2017 Edition		∍ No.	
	!	Performance Eval	uation Sheet			
Tasks	•				1st	2nd
	Describes three components of	f an effective debriefing	 J			2110
2.	* Describes key topics of an eff	ective debriefing				
	Describes when debriefing sho	uld take place				
	Describes who should be involved	ved in debriefing				
* Critic	cal Step Failure of this step man failure on the entire obje	ndates ective Safety is Par		number steps candid	late	3

Rev. 9/10/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill N	lo. HMT- :	38B	Primary Task:	Assisti	ng in th	e Incident	Critique					
Objective(s): 7.6.1(B)				NFPA Standard: Candida 1072, 2017 Edition		Candidate	No.					
Performance Evaluation Sheet												
Tasks	s:							1st	2nd			
1.	Describes t	hree co	emponents of an effe	ctive critique								
2.	* Describes key topics of an effective critique											
3.	Describes why an effective critique is necessary after a HMWMD incident											
4.	Describes which written documents should be prepared as a result of the critique											
* Critical Step		Step Failure of this step mandates failure on the entire objective		Safety is Paramount		Total number steps candidate must complete to pass			3			

Rev. 9/10/18



State of Connecticut COMMISSION ON FIRE PREVENTION AND CONTROL



Hazardous Materials Technician

Skill No. HMT-38C Primary Task: Reporting and Documenting the Incident											
Objective(s): 7.6.1B					NFPA Standard: Candidat 1072, 2017 Edition						
Performance Evaluation Sheet											
Tasks	»:						1st	2nd			
1.	Identifies r SOP	eports a	and supporting docun	nentation required by emergend	cy response p	lan or					
2.	* Demonstrates completion of reports required by emergency response plan or SOP										
3.	Describes	importa	ance of personnel exp	posure records							
4.	Describes	importa	ance of debriefing rec	ords							
5.	Describes importance of critique records										
6.	Identifies steps in keeping an activity log and exposure records										
7.	Identifies steps to be taken in compiling incident reports for federal, state, local and organizational requirements										
8.	Identifies requirement for compiling hot zone entry and exit logs										
9.	Identifies requirements for compiling personal protective equipment logs										
10.	* Identifies requirements for filing documents and maintaining records										
* Critical Step Failure of this step mandates failure on the entire objective				Safety is Paramount	Total number steps candidate must complete to pass			7			

Rev. 9/10/18