

DMV MODIFIED OFF-ROAD
CHECK LIST
WETHERSFIELD LANE

Name _____ Make _____ Model _____

Year _____ Vin # _____ Passed _____ Rejected _____

- 1 Muffler- prevent any unusual of excessive exhaust noise
(14-80b)

- 2 Reflector- 1 rear red reflector, may be part of rear
taillamp assembly. Mounted from 15" to 60" from the
ground and visible at night from all distances of 100' to 300 ft. when directly
infront of upper beams of headlamps. (14-96d-b)

- 3 Fenders- Over the front and rear wheels. Lower edge of
the rear fender may not be greater than 14" above the
rear axle, when measured with out weight of rider
applied to seat. A mud flap on the rear fender may be
used to bring the fender into compliance

- 4 Tires- Must have alt least 2/32nds" center tread. Tire
sidewalls will be inspected and if the wording "Not For
Highway use" or "Off Road Use Only" is found,
vehicle is rejected. If indications of that the previously
mentioned wording has been buffed off, the registrant
will be required to obtain a letter from a dealer
certifying "Safe for Road Use" for make, model and
size of tire in question.
the following defects will also be caused for rejection
 - a- No tread
 - b- Bulges
 - c- Cuts or snags in excess of One (1) inch on the outside
of tire.

- 5 Chain Guard- Chainguard is required to protect the
OPERATORS foot while on the foot peg. In addition,
If motorcycle is equipped with passenger foot pegs
Then chain guard must protect this area.

- 6 Battery- Battery must be adequate to operate one (1)
front white and (1) one rear red light with engine
STOPPED. must be securely mounted. Maintanaence
Of battery will be the owner/rides responsibility.

- 7 Speedometer- Speedometer is required. Digital's switch between speedometer and odometer mode are acceptable.
- 8 Display Of Numbered Plate- Number plate shall be displayed in a horizontal position, fastened so as not to swing and be so located as to be illuminated by marker lamp. (14-96c)
- 9 Headlamp- Headlamp may be single or multiple beam. If multiple beam it must have a high-beam indicator. It shall be securely mounted and properly aimed. (14-96b)
- 10 Tail Lights And Stop Light- At least one Red tail lamp and one stop light. Visible from 1000 ft. and not less than 300' from the rear, mounted from 15" to 72 " from the ground.
The rear number plate must be illuminated with a white light and visible from a distance of 50' (14-96c)
- 11 Turn Signal- Turn signals must be mounted on the front and rear of the vehicle. They must be amber in front and amber or red in the rear. Front turn signal shall be a minimum distance of 16" apart (center to center) Or 4" (edge to edge) from the head light. The rear lights shall have a minimum distance of 9" (center to center) or 4" (edge to edge) when mounted with a stop light in between. Measured vertically center.
(49-571-108) (14-96e(b))
- 12 Original Identification Number Or Vehicle
Must be cleaned so it can be checked by the Inspector.
- 13 Mirror- Mirror is required to show the roadway to the rear of the vehicle. It shall be free of blemishes, untarnished and unbroken and shall have no defects which would prevent an adequate rear view of the highway. It shall be properly mounted and securely fasten to prevent vibration.

13. **Horn**- Horn switch/button, shall be securely mounted so as to be easily accessible to operator of vehicle. Shall be audible, under normal conditions for not less than 200 feet. The horn shall be electrical or squeeze bulb type if metal horn construction and must be activated on the left side of handlebar. No unreasonable loud or harsh sounds or whistle. (14-80e)

14. **Brakes**-Brakes shall be provided on at least one wheel of each motorcycle prior to 1974. Motorcycles designated as a 1974 or later model shall be equipped with brakes on front and rear wheels. Brakes shall meet requirements of Sec. 14-80h (14-80D)